


LH1399IC - IC DOUBLE WALL HOUSING

3" LOW VOLTAGE HOUSINGS



SPECIFICATION

12V Out 50W Max MR16

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired housing adjusts up to a 1 1/4" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Trim is secured with torsion wing springs.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box: 16 gauge pre-wired galvanized steel Junction Box, 25 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (5) 3/4", (1) 1" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: IC rated housing rated for direct contact with low to medium density loosefill blown and rolled insulation. For use with high density loosefill blown insulation, reduce rated lamp wattage accordingly (roughly %15-%20).

Airflow: Airtight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: cETL Listed

COMPATIBILITY

 LR1383 PULL DOWN ADJUSTABLE BAFFLE	 LR1387 DECORATIVE PULL DOWN	 LR1356 DECO GLASS
 LR1311 LOUVER	 LR1371 REFLECTOR WALL WASH	 LR1373 BAFFLE WALL WASH
 LR1320 SLOT	 LR1367 PULL DOWN	 LRSQ1317 TRIM W/ FROSTED LENS
 LR1321 REFLECTOR	 LR1352 DECO GLASS PANEL	 LR1397 MR16 PULL DOWN
 LR1317 REFLECTOR W/ FROSTED LENS (T LAMP)	 LR1319 PINHOLE W/ REFLECTOR	 LR1393 BAFFLE

Please see website for more compatible items.

FEATURE:



ORDERING EXAMPLE : LH1399ICA

LH1399IC	RATING	WATTAGE	VOLTAGE	ACCESSORIES
LH1399IC	A :IC-Airtight	Blank :50W	Blank :120V/12V	/LBL20 :20W Derating
	AE :Airtight Electronic		-27 :277V/12V	/LBL35 :35W Derating

ID #: 247