

TYPE CATALOG#

LR1461 - PINHOLE W/ REFLECTOR

4" LOW VOLTAGE TRIMS











SPECIFICATION

12V 75W Max MR16 GU5.3

Application: These narrow aperture beams allow a defined location to be lit without affecting the surrounding surfaces while concealing the lamp image and providing a consistent ceiling appearance. The smaller the apperture the more confined the illumination. **Pinhole** trims provide the type of precise illumination needed for artwork such as paintings and statues. They are also ideal for cozy environments like restaurants and living spaces where glare-free illumination is desired. Aside from accent lighting, they can also be utilized for task lighting applications such as above tables, workspace, cabinetry, and other locations where a directed beam is desired.

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling

Lens Inclusion: Clear glass protective safety lens included in packaging.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Reflector Finish: Spun Aluminum Reflector Available in White, Black, Clear, Gold, All Copper*, All Mocha* and Satin Haze.

Ring Finish: Die-Formed Aluminum Trim Ring Available in White, Black, Chrome, Natural, Copper and Mocha.

Accessories: Takes (1) 2" Media. Label: UL Listed, cETL Listed

COMPATIBILITY

<u>LH1499</u>	<u>LH1499IC</u>	<u>LH1499R</u>
STANDARD HOUSING	IC DOUBLE WALL Housing	REMODEL HOUSING 120V/277V
<u>LSH1499</u>	<u>LSH1499IC</u>	<u>LSH1499R</u>
SHALLOW HOUSING	SHALLOW IC HOUSING	SHALLOW REMODEL Housing

Note: Wattage limitations on compatible items must be met.

FEATURE:













ORDERING EXAMPLE: LR1461W

LR1461	REI	FLECTOR FINISH	RING	FINISH	ACCESSORIES	
LR1461	W	:White	Blank	:White	/L38	:Clear Lens
	В	:Black	В	:Black	/L40	:Yellow Lens
	C	:Clear	С	:Chrome	/L41	:Blue Lens
	G	:Gold		:Natural	/L42	:Amber Lens
	S	:Satin Haze	CO	:Copper	/L43 /L44	:Green Lens
			MO	:Mocha	/L44	:Daylight Blue Lens :Lens with Internal Louver Filter
					/L48	:Lens with Internal Louver Filter
						:Frosted Soft Focus
					/L50UV	:UltraViolet Filter
					/L53	:Micro - Prismatic Spread Lens :Linear Spread Lens
					/L55	:Linear Spread Lens
					/LL16B	:Black
					/LL16C	:Clear

ID#: 218

