


LREBLD5602 - 5" & 6" LED REFLECTOR (1100LM)

5" & 6" LED



SPECIFICATION

LED

Application: 6" General Purpose LED Trim with Orange Push-In Quick Connector Base is perfect for Retrofit, New Construction and Remodel Applications in low to medium height ceilings.

Mounting: Mounts into standard 5 & 6" General Purpose Recessed housing with steel pressure springs mounted on trim to ensure positive retention inside housing. Alternate mounting methods available, consult factory.

Power Connection: Comes standard with socket mounted to top of fixture. Meets CA Title 24 Requirements and other standards restricting the use of Medium Base or Bi-Pin Sockets.

Lumen Maintenance: Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, finned heat sink design for maximum heat rejection to provide long LED life.

Driver: Electronic Direct Current driver mounted on fixture.

Dimming: Smoothly dims down to 5% of initial light output with flicker-free performance. Works with standard incandescent dimmers. Factory qualified for use with Lutron brand dimmers: S600PR, DVSCCL-153P & DV600PR as well as Leviton IP106-600W. Works with standard electronic low voltage (ELV) dimmers. Factory qualified for use with Lutron brand dimmers: SELV300P, DVELV-300P, MAELV-600 and NELV-450.

Safety Labels: ETL/CETL listed. UL listed for wet locations. NYC approved: Calendar#41937. High Efficacy Luminaire Certified by the California Energy Commission (CEC) as Title 24 / JA8 Compliant.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Finish: Available in Black Reflector/Black Ring* and White Reflector/ White Ring.

Color Temp: Available in 2700K, 3000K, 3500K* and 4000K. Binned according to ANSI C78 377A for color temperature and chromaticity ranges. Consult factory as extended lead times and minimum order quantities apply.

Adapter: Available in and Med Base.

COMPATIBILITY

 LH7ICA-QC NEW CONSTRUCTION (2-PIN)	 LH7RICA-QC REMODEL HOUSING (2-PIN)	 LH27 STANDARD SHALLOW E26 HOUSING
 LH5 STANDARD NEW CONSTRUCTION HOUSING	 LH5R STANDARD REMODEL HOUSING	

Note: Wattage limitations on compatible items must be met.

LED Details:

16W 1100 Lumen Package
Color Rendering Index (CRI)²: 90
Color Temperature: 3,000K
Lamp Equivalent: 75W R30

Benefit:

- 16 watt trim fits standard 5" and 6" housings
- Fully die-cast for long lasting durability
- Trims are UL listed for wet locations
- Quick Ship Item - Readily Available
- 90 CRI Standard

Title 24/JA8 Compliant

- LREBLD5602 -T27
- LREBLD5602 -T30
- LREBLD5602 -T40

Energy Star Qualified

- LREBLD5602 -T27
- LREBLD5602 -T30
- LREBLD5602 -T40

FEATURE:



ORDERING EXAMPLE : LREBLD5602W-T27

LREBLD5602	FINISH	VOLTAGE	COLOR TEMP	ADAPTER
LREBLD5602	B :Black Reflector/Black Ring*	Blank :120V	-T27 :2700K	Blank :None
	W :White Reflector/ White Ring	UE :120V/277V**	-T30 :3000K	/SQG4-MED :Med Base
			-T35 :3500K*	
			-T40 :4000K	

* Special Order Item. Consult Factory for stock.

** Only dimmable in 120V.