


## LRESQLD402 - SQUARE/SQUARE (DIMMABLE)

4" LED



## SPECIFICATION

LED 11W/16W

**Application:** 4" General Purpose Square LED Trim with Orange Push-In Quick Connector Base is perfect for Retrofit, New Construction and Remodel Applications in low to medium height ceilings.

**Mounting:** Mounts into standard 4" General Purpose Recessed housing cans with steel pressure springs mounted on trim to ensure positive retention inside housing. Alternate mounting methods available, consult factory.

**Power Connection:** Comes standard with socket mounted to top of fixture. Meets CA Title 24 Requirements and other standards restricting the use of Medium base or Bi-Pin Sockets.

**Lumen Maintenance:** Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

**Thermal Management:** Effective thermal dissipation facilitated by integral cast-aluminum, finned heat sink design for maximum heat rejection to provide long LED life.

**Driver:** Electronic Direct Current driver mounted on fixture. Comes standard with Incandescent dimming. Smoothly dims down to 5% with standard Incandescent and Low Voltage dimmers.

**Safety Labels:** ETL/CETL listed. UL listed for wet location. NYC approved: Calendar#41937.

**Warm Dimming:** With this new technology you can create the warm glow of traditional incandescent dimming, while offering extraordinary energy efficiency and service life of LED Lighting. Allow for fixture start at a full 3000K when at full-brightness and smoothly dim down to 5% level with the warm glow of 2200K using ELV dimming.

**Warranty:** Covered by a 5 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

**Finish:** Available in White Reflector/White Ring and White Reflector/Chrome Ring.

**Color Temp:** Available in 2200K-3000K Warm Dimming, 2700K, 3000K, 3500K and 4000K. Binned according to ANSIC78 377A for color temperature and chromaticity ranges. Consult factory as extended lead times and minimum order quantities apply.

## COMPATIBILITY

[LH99ICA-2P-ORANGE-CONNECTOR](#)[LH99RICA-QC](#)[LSH99ICA-QC](#)[LSHFR99-QC](#)

**4" IC 2HR FIRE-RATED LED HOUSING (SHALLOW)**

Note: Wattage limitations on compatible items must be met.

## LED Details:

## 11W 600 Lumen Package

Color Rendering Index (CRI)<sup>2</sup>: 85  
Color Temperature: 3000K

Lamp Equivalent: 65W BR30/50 A19

## 16W 900 Lumen Package

Color Rendering Index (CRI)<sup>2</sup>: 85  
Color Temperature: 3000K  
Lamp Equivalent: 75W R40

## Benefit:

- New Warm Dimming Option
- Fully die-cast for long lasting beauty
- Trims are UL listed for wet locations
- Quick Ship Item - Readily Available
- ELV/Incandescent Dimming Standard
- Energy Star Qualified
- 5 year limited warranty

## FEATURE:



ORDERING EXAMPLE : LRESQLD402WC-T27

LRESQLD402	FINISH	VOLTAGE	COLOR TEMP	LUMENS	RATING	ADAPTER
LRESQLD402	W :White Reflector/White Ring	Blank :120V	-DWM :2200K-3000K Warm Dimming	Blank :600 Lumen (11W)	Blank :None	Blank :None
	WC :White Reflector/Chrome Ring	UE :120V/277V	-T27 :2700K	-L10 :900 Lumen (16W)	-WL :Wet Location	/SQG4-MED :Med Base
	BB :Black Reflector/Black Ring		-T30 :3000K			
	BN :Black Reflector/Natural Ring		-T35 :3500K			
			-T40 :4000K			