



LRLD1319 - 3" MICRO-CAST PINHOLE (500LM) 3" LED TRIMS



SPECIFICATION

10W LED

Application: This miniature general purpose LED Pinhole trim is perfect for low to medium height ceilings in residential and light commercial applications. Its small aperture makes it ideal for strategic placement when tight beam spread control is required and energy savings is important. A variety of finishes and beam spreads are available to achieve a desired look.

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.

Power Connection: LED heat sinked lamp module is replaceable via onboard quick exclusionary disconnect terminal. No tools required. Meets CA Title 24 Requirements and other standards restricting the use of Medium Base or Bi-Pin Sockets.

Lumen Maintenance: Minimum 35,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.


Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, finned heat sink design for maximum heat rejection to provide long LED life.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Finish: Die-cast aluminum Ring. Available in All Black, Black Reflector/Copper Ring, Black Reflector/Mocha Ring, Black Reflector/Natural Ring and Black Reflector/White Ring.


Color Temp: Available in 2700K (90CRI), 3000K (90CRI), 3500K (90CRI) and 4000K (90CRI).

COMPATIBILITY




LHFRLD39C20

3" FIRE-RATED LED HOUSING (700LM)



LHLD39C20

3" LED NEW CONSTRUCTION HOUSING (700LM)



LHLD3R9C20

3" LED REMODEL HOUSING (700LM)

Note: Wattage limitations on compatible items must be met.

LED Details:

10W 500 + Lumens Delivered
Color Rendering Index (CRI): 90
Color Temperature: 3,000K
Lamp Equivalents: 50W MR16

Benefit:

- Up to 500 Lumens Delivered!
- Budget Friendly, specification quality performance
- Small aperture for hard to light spaces
- Singular diode, no multiple LEDs
- 90CRI standard for better color rendering



ORDERING EXAMPLE : LRLD1319BW-DL

LRLD1319	FINISH	COLOR TEMP	OPTIONS
LRLD1319	BB :All Black	Blank :3000K (90CRI)	Blank :None
	BCO :Black Reflector/Copper Ring	-T27 :2700K (90CRI)	-WL :Wet Location
	BMO :Black Reflector/Mocha Ring	-T35 :3500K (90CRI)	
	BN :Black Reflector/Natural Ring	-T40 :4000K (90CRI)	
	BW :Black Reflector/White Ring		