


LRQ1481 - SQUARE RING PULL DOWN 4" LOW VOLTAGE TRIMS



Not for use with Remodel Housings.

SPECIFICATION

12V 75W Max MR16 GU5.3

Socket: 2 pin porcelain socket included with trim. Some wiring required.

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.

Lens Inclusion: Clear glass protective safety lens included in packaging.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Finish: Available in White, Black, Natural, Copper and Mocha.



COMPATIBILITY

 LH1499 STANDARD HOUSING	 LH1499IC IC DOUBLE WALL HOUSING	 LH1499R REMODEL HOUSING 120V/277V
 LSH1499 SHALLOW HOUSING	 LSH1499IC SHALLOW IC HOUSING	

Note: Wattage limitations on compatible items must be met.

FEATURE:



ORDERING EXAMPLE : LRQ1481B

LRQ1481	FINISH	ACCESSORIES
LRQ1481	W :White	/L38 :Clear Lens
	B :Black	/L40 :Yellow Lens
	N :Natural	/L41 :Blue Lens
	CO :Copper	/L42 :Amber Lens
	MO :Mocha	/L43 :Green Lens
		/L44 :Daylight Blue Lens
		/L48 :Lens with Internal Louver Filter
		/L49 :Frosted Soft Focus
		/L50UV :UltraViolet Filter
		/L53 :Micro - Prismatic Spread Lens
		/L55 :Linear Spread Lens
		/LL16B :Black
		/LL16C :Clear

ID#: 245