


LRSQD1319 - 3" SQUARE PINHOLE BAFFLE (600LM/1000LM) 3" LED TRIMS



SPECIFICATION

10W/13W LED

Application: This miniature general purpose LED Square trim is perfect for low to medium height ceilings in residential and light commercial applications. Its square aperture and integral baffle integrates perfectly with today's modern design environments.

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.

Power Connection: LED heat sinked lamp module is replaceable via onboard quick exclusionary disconnect terminal. No tools required. Meets CA Title 24 Requirements and other standards restricting the use of Medium Base or Bi-Pin Sockets.

Lumen Maintenance: Minimum 35,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, finned heat sink design for maximum heat rejection to provide long LED life.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Safety Labels: ETL/cETL listed. Suitable for damp locations only.

Finish: Available in All Black, Black Baffle/Chrome Ring, Black Baffle/Mocha Ring, Black Baffle/Natural Ring and Black Baffle/White Ring.

Color Temp: Available in 2700K (90CRI), 3000K (90CRI), 3500K (90CRI) and 4000K (90CRI).

Assembled in USA

COMPATIBILITY



LHFRLD39C20

3" FIRE-RATED LED HOUSING (700LM)



LHLD39C20

3" LED NEW CONSTRUCTION HOUSING (700LM)



LHLD39C20

3" LED REMODEL HOUSING (700LM)

Note: Wattage limitations on compatible items must be met.

LED Details:

10W 600 + Lumens Delivered
Color Rendering Index (CRI): 90
Color Temperature: 3,000K
Lamp Equivalents: 50W MR16

13W 1000 + Lumens Delivered
Color Rendering Index (CRI): 90
Color Temperature: 3,000K
Lamp Equivalents: 75W MR16

Benefit:

- New 1000lm option!
- Budget Friendly, specification quality performance
- Small aperture for hard to light spaces
- Singular diode, no multiple LEDs
- 90CRI standard for better color rendering

FEATURE:



ORDERING EXAMPLE : LRSQD1319BW-T35

LRSQD1319	FINISH	COLOR TEMP	LUMENS
LRSQD1319	BB :All Black	Blank :3000K (90CRI)	Blank :600lm (10W)
	BC :Black Baffle/Chrome Ring	-T27 :2700K (90CRI)	-L10 :1000lm (13W)
	BMO :Black Baffle/Mocha Ring	-T35 :3500K (90CRI)	
	BN :Black Baffle/Natural Ring	-T40 :4000K (90CRI)	
	BW :Black Baffle/White Ring		

ID#: 3223