



LSH1499 - SHALLOW HOUSING

4" LOW VOLTAGE HOUSINGS



SPECIFICATION

12V Out 37W Max MR16

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired housing adjusts up to a 1 1/4" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Transformer: High quality insulated transformer installed adjacent to Junction Box, bottom and top accessible. Thermally protected rated for 90° C. Available in magnetic or "noise-free" electronic.

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box: 16 gauge pre-wired galvanized steel Junction Box, 25 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (3) 3/4", (1) 1" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non IC rated housing must be kept 3" from insulation. IC rated housing rated for direct contact with low to medium density loosefill blown and rolled insulation. For use with high density loose fill blown insulation, reduce rated lamp wattage accordingly (roughly %15-%20).

Safety Labels: ETL/CETL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: cETL Listed

COMPATIBILITY

 LR1409 ADJUSTABLE GIMBAL	 LR1467 ADJUSTABLE PULL DOWN	 LRQ1481 SQUARE RING PULL DOWN
 LR1423 FROSTED GLASS DOME	 LR1424 SHOWER DECO GLASS (FROSTED RING)	 LR1443 PINHOLE W/ BAFFLE
 LR1445 WALL WASH REFLECTOR EYELID	 LRQ1423 SQUARE RING DOME	 LR1481 PULL DOWN W/ REFLECTOR
 LR1493 METAL BAFFLE	 LRQ1471 SQUARE RING WALL WASH REFLECTOR	 LR1468 MULTI ACCESSORY PULL DOWN
 LR1435 ADJUSTABLE SPOT	 LR1466 ADJUSTABLE GIMBAL	 LR1480 ADJUSTABLE PULL DOWN W/ SNOOT

Please see website for more compatible items.

FEATURE:



ORDERING EXAMPLE : LSH1499

LSH1499	RATING	WATTAGE	VOLTAGE	ACCESSORIES
LSH1499	Blank :Non-IC Magnetic E :Non-IC Electronic	Blank :37W	Blank :120V -27 :277V (Electronic*)	/LBL20 :20W Derating /LBL35 :35W Derating

* Available with 120V/277V Magnetic Option, consult factory

ID#: 194