


LT123 - DECO
 LOW VOLTAGE DROP TRACK

SPECIFICATION

12V 50W T4/T3 GY6.35

Connector: Comes standard with 3-Wire H-Type thermo-plastic track connections. Fixture is factory preset for installation on single-circuit track. Contacts may be easily adjusted to install on two-circuit track via pull-up tab. J-Type and L-Type connections are available with extended lead times - consult factory.

Transformer: Solid state electronic transformer for voltage reduction and noiseless operation. 120V/60Hz input - 12V output. 50 VA max. load. (Unless specified otherwise) For dimming, use electronic low voltage rated dimming controls. When using dimmer controls, it is recommended to fully power lamps without dimming for 50+ hours to maximize halogen lamp life.

Shade Glass: Fixture in Standard Available in Blue, Frosted White, Green and Yellow. Fixture in standard natural raw metal. Glass shade in frosted white, blue, yellow or green. Cord in standard white, black or metal.

Wire Length: Available in 12", 24", 36", 48", 60" and 72".

Cable Color: Available in White Cable and Connector, Black Cable and Connector and Metalic Cable and Black Connector.

Label: UL Listed

COMPATIBILITY


LP



LPC

1 CCT TRACK CHANNEL

2 CCT TRACK CHANNEL

Note: Wattage limitations on compatible items must be met.

FEATURE:


ORDERING EXAMPLE : LT123-BL-12W

LT123	SHADE GLASS	WIRE LENGTH	CABLE COLOR
LT123	-BL :Blue	-12 :12"	W :White Cable and Connector
	-FR :Frosted White	-24 :24"	B :Black Cable and Connector
	-GR :Green	-36 :36"	MC :Metalic Cable and Black Connector
	-YL :Yellow	-48 :48"	
		-60 :60"	
		-72 :72"	

ID# : 818