


LTD7215 - 15W DIE-CAST AZTEC 16 LED LED TRACK HEAD



Available in Bright White. Consult factory.

SPECIFICATION

120V AC 7 x 2.1W LED

Application: Architecturally styled Aztec LED track head features a fully die-cast housing with concealed heat sink, hardware and wiring for a sleek, unobtrusive appearance. Its cosmetic design matches other Aztec track heads including HID, T6, MR16 and PAR lamp models. Perfect for retail and commercial applications where energy efficiency and powerful lumen output is required in an elegant design.

Connector: LITON track fixtures come standard with 3-Wire H-Type track connections. Fixture is factory preset for installation on single-circuit track. J-Type and L-Type connections are available with extended lead times - consult factory.

Driver: Electronic Constant Current driver integrally mounted in fixture casing.

Dimming: Low Voltage dimming option (-DLV) works with standard Electronic Low Voltage Dimmers. Factory qualified for use with LUTRON Brand Dimmers: SELV-300P, VELV-300P, NELV-450 along with 3-Way versions. (-DLV) Dimming Option also compatible with Grafik Eye Dimming Interface ELVI-1000, smoothly dims down as low as 10% of initial light output with flicker-free operation.

Lumen Maintenance: Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, heat sink design for maximum heat rejection to provide long LED life.

Color Temperature: LED Diodes comes standard in warm white 3,000K +/- 100K. Also available in 4,000K as special order. Consult factory, extended lead times and minimum order quantities may apply.

Safety Labels: UL listed. Suitable for dry locations only.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Finish: Available in Black (3000K), Bright White (3000K) and Bright White (4000K).

Beam Spread: Available in 25° Narrow Flood and 45° Flood.

Extension: Available in 12", 24", 36" and 48".

Label: UL Listed



COMPATIBILITY



LP

1 CCT TRACK CHANNEL



LPC

2 CCT TRACK CHANNEL

Note: Wattage limitations on compatible items must be met.

LED Details:

15W 1000 Lumens Delivered

Color Rendering Index (CRI): 80

Color Temperature: 3,000K

Lamp Equivalents: 75W PAR20 FL, 75W MR16 FL

Benefit:

- Die-cast aluminum housing
- Concealed heat sink, hardware and wiring
- For use with standard H-Style 1 circuit and 2 circuit track
- ELV Dimming option
- Precision design insures firm positioning

FEATURE:



ORDERING EXAMPLE : LTD7215B

LTD7215	FINISH	BEAM SPREAD	EXTENSION	DIMMING
LTD7215	B :Black (3000K)	Blank :45° Flood	Blank :None	Blank :Non-Dimming
	W :Bright White (3000K)	-B25 :25° Narrow Flood	-12 :12"	-DLV :Dimming
	W-T40 :Bright White (4000K)		-24 :24"	
			-36 :36"	
			-48 :48"	

ID#: 2608