

LUMEN PAD

ROUND AND SQUARE | 5" & 7" ROUND • 5" & 7" SQUARE

LITON is proud to introduce our new super-sleek, super-slim, surface-mount 5" & 7" Square, as well as 5" & 7" Round Lumen Pads! Offering a unique combination of innovative, elegantly minimalist design & high quality LED performance, these ultra-low-profile luminaires are the ideal, easy-install alternatives to recessed lighting for plenum-challenged spaces with low-to-medium (average) ceiling heights.

Color Temperature

Comes standard with 3,000K Warm White, 3500K Neutral, or 4000K Cool White LED's binned according to ANSI C78 377A for color temperature and chromaticity ranges.

Thermal Management

Effective thermal dissipation facilitated by integral heat sink design for maximum heat rejection to provide long LED life.

Driver



Smoothly dims down to 5% with standard Low Voltage dimmers. Works with standard electronic low voltage (ELV) dimmers. Factory qualified for use with Lutron brand dimmers: **SELV300P**, **DVELV-300P**, **MAELV-600** and **NELV-450**.

Warranty

Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Benefits

- 85CRI, 120V AC input
- 3 color temperature options: 3000K, 3500K and 4000K
- **Die cast** aluminum construction
- Mounts to junction box

Lumen Maintenance

Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Square Lumen Pad

Mounting

Universal mounting hardware allows mounting to all standard octagonal electrical junction boxes.

Wet Location

Suitable for Wet Location Installations.




LUMEN PAD

ROUND AND SQUARE | 5" & 7" ROUND • 5" & 7" SQUARE

Application

5" and 7" Architectural Surface Mount Downlight is perfect for Retrofit, New Construction and Remodel applications in low to medium height ceilings. Super thin profile is unobtrusive in design and has low glare.

LUMEN PAD ROUND 12W • 1,000LM - 15W • 1,200LM




ORDERING 5" & 7" LUMEN PAD ROUND

Example: LCMPD7RWUE-D10-T35-PC

ITEM	FINISH	DIMMING	COLOR TEMPERATURE	MATERIAL
LCMPD5R : 5-inch round, 1,000Lm	W : White	Blank : ELV Dimming	-T30 : 3000K	Blank : Die-Cast Aluminum
LCMPD7R : 7-inch round, 1,200Lm		UE-D10 : 120V/277V (0-10V Dimming)	-T35 : 3500K	-PC : Non-Conductive Polycarbonate*
			-T40 : 4000K	

* Special order.

LUMEN PAD SQUARE 12W • 700LM - 15W • 900LM



ORDERING 5" & 7" LUMEN PAD SQUARE

Example: LCMPD7QW-T35-PC

ITEM	FINISH	DIMMING	COLOR TEMPERATURE	MATERIAL
LCMPD5Q : 5-inch square, 700Lm	W : White	Blank : ELV-Dimming	-T30 : 3000K	Blank : Die-Cast Aluminum
LCMPD7Q : 7-inch square, 900Lm			-T35 : 3500K	-PC : Non-Conductive Polycarbonate*
			-T40 : 4000K	

* Special order.