


miniARC
4"


LED Phantom Trimless Downlight

Phantom die-cast trims sit flush to the ceiling to provide a flat, clean, unobtrusive appearance. This housing is **IC-Rated**.




- 1** HOUSING PAINTED BLACK to reduce stray light
- 2** INTERNAL GASKETING of power supply to eliminate vibration noise
- 3** EASY ACCESS power supply mounted inside box for easy maintenance
- 4** FULLY DIE-CAST TRIMS Architectural Trims
- 5** DIE-CAST PLASTER FRAME for seamless integration with ceiling
- 6** PRE-SET MOUNTING HOLES for 1/2", 5/8", 3/4", 1" ceiling thickness for easy installation
- 7** ADJUSTABLE 24" HANGER BARS included with housing

3-Step Easy Installation ...




1

Cut appropriate hole for plaster trim ring and set height of ring based on ceiling thickness.



2

Apply plaster tape and compound around plaster trim ring and even out any rough edges.



3


Install die-cast lighting trim, by simply pushing it in.

4" Phantom LED Trimless

LHXLD412C35 | FLUSH TRIM | 600 LUMEN

APPLICATIONS


Designed for low to medium ceiling heights in retail, hospitality, commercial and high-end residential applications, Phantom die-cast trims sit flush to the ceiling to provide a flat, clean, unobtrusive appearance.

LRX4LH19
PinholeLRX4LH20
SlotLRX4LH21
ReflectorLRX4LH22
LensedLRX4LH73
Adjustable AccentLRX4LH75
Wall Wash

ARCHITECTURAL SPECIFICATIONS



Lumen Packages	12W, Up to 600 Lumens
CCT	3000K Standard, Binned to 3-Step MacAdam Ellipses (SDCM) 2700K, 3500K and 4000K Optional binned to ANSI Standard.
CRI	80+ CRI, 90+ CRI Optional
Lumen Maintenance	50,000 Hrs.. L70 life based on ANSI TM-21 calculations from LM80 Standardized tests.
IC Rating	Rated for Insulation Contact and rated as Airtight
Dimming Options	ELV 5%, Incandescent 5%
Emergency Options	EM: 5W, Includes Remote Test Switch, plate cover and j-box.
Input	120V, 120V/277V Universal Option



PHOTOMETRY


INTENSITY (CANDLEPOWER) SUMMARY

ANGLE	LUMINANCE
0	1638.36
20	577.23
40	34.63
60	2.94
80	0.19

ZONAL LUMEN SUMMARY

ZONE	LUMENS	%LUMINAIRE
0-20	394.92	64.00
0-30	543.24	88.00
0-40	593.17	96.10
0-60	615.91	99.80
0-90	617.44	100.00

CANDLEPOWER DISTRIBUTION



ORDERING

Example: LHXLD412C35-DIN / LRX4LH19W

HOUSING	DRIVER TYPE*	TRIM	FINISH	BEAM SPREAD	CRI
LHXLD412C35 NEW CONSTRUCTION	Blank: 120V Non Dimming UE: 120V/277V Non Dimming UE-D10: 120V/277V 0-10V Dimming -DIN: Incandescent/ELV Dimming -DHL: HiLume Dimming 120V/277V **	/ LRX4LH19 : Pinhole / LRX4LH20 : Slot / LRX4LH21 : Reflector / LRX4LH22 : Lensed / LRX4LH73 : Adj. Accent / LRX4LH75 : Wall Wash	W: White	Blank: Narrow Flood -B45: Flood -B60: Wide Flood	Blank: 80+ -C90: 90+

* Add "EM" for Emergency Option ** Not available for Remodel. Only dims in 120V.