


LCD7415 - APOLLO 15 CANOPY MOUNT - 1500 LUMEN LED TRACK HEAD



SPECIFICATION

120V 21W LED

Application: High Output architecturally-styled APOLLO LED Trackhead is perfect for applications where powerful lumen output is required. Fully die-cast with integrated heatsink, hardware and wiring for a sleek unobtrusive appearance. APOLLO combines long-lasting beauty and energy efficiency with intense lumen output. Excels at delivering maximum footcandles to objects, spaces and features from longer distances. Ideal for Retail and Commercial applications.

Mounting: Fixture includes a mounting bracket for installation directly to a 4" octagonal electrical junction-box.

Driver: Electronic Constant Current driver integrally mounted in fixture casing.

Dimming: Low Voltage dimming option (-DLV) works with standard Electronic Low Voltage Dimmers. Factory qualified for use with LUTRON Brand Dimmers: SELV-300P, VELV-300P, NELV-450 along with 3-Way versions. (-DLV) Dimming Option also compatible with Grafik Eye Dimming Interface ELVI-1000, smoothly dims down as low as 10% of initial light output with flicker-free operation. (-DUN) option is a universal dimming driver Uni-Dim™ that works with most ELV, incandescent and 0-10V fluorescent dimmers.

Lumen Maintenance: Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, heat sink design for maximum heat rejection to provide long LED life.

Warranty: Covered by a 5 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Finish: Available in All Black and Bright White/Black Heat Sink.

Beam Spread: Multifaceted glare reducing anodized reflector held in place with die-cast aluminum holder. Available in Flood, Narrow and Spot. Optical reflectors can be ordered separately. Use part #: RL-AP15-FL, RL-AP15-NF, RL-AP15-SP

Color Temp: Available in 2700K, 3000K, 3500K, 4000K and 6500K. LEDs binned to within 3-Step MacAdam Ellipses (SDCM) and surpasses the ANSI C78 377A standard for color deviation.

LED Details:

21W 1500 + Lumens Delivered

Color Rendering Index (CRI): 80

Lamp Equivalents: 75W MR16, 90W PAR30, PAR38, 20W CMH-PAR20

Benefit:

- Fully die-cast for high quality, long-lasting beauty
- 3 beam spread options for fine tuning footcandle distribution
- Powerful 1500 lumen output lights objects and spaces near and far
- MR16 75W performance in a long life, cool running LED track head
- Available with Tool-less field changeable optics
- 0-10V, ELV or 3-Wire dimming options

FEATURE:




ORDERING EXAMPLE : LCD7415B-B15UE-DUN-T27

LCD7415	FINISH	BEAM SPREAD	DIMMING	COLOR TEMP	CRI
LCD7415	B :All Black	-B15 :Spot	Blank :120V Non-Dimming	-T27 :2700K	Blank :80 CRI
	W :Bright White/Black Heat Sink	-B25 :Narrow	UE-DUN :120V/277V ELV/2-Wire/0-10V Dimming	-T30 :3000K	-C90 :90 CRI*
		-B45 :Flood		-T35 :3500K	
				-T40 :4000K	
				-T65 :6500K	
				-TWD :1850K-2700K	
				Warm Dimming	

* Special Order
Available with 277V input & Multi-Circuit Track. Consult Factory.

ID#: 3260

LCD7430 - APOLLO 30 CANOPY MOUNT - 2900 LUMEN LED TRACK HEAD



SPECIFICATION

120V 32W LED

Application: High Output architecturally-styled APOLLO LED Trackhead is perfect for applications where powerful lumen output is required. Fully die-cast with integrated heatsink, hardware and wiring for a sleek unobtrusive appearance. APOLLO combines long-lasting beauty and energy efficiency with intense lumen output. Excels at delivering maximum footcandles to objects, spaces and features from longer distances. Ideal for Retail and Commercial applications.

Mounting: Fixture includes a mounting bracket for installation directly to a 4" octagonal electrical junction-box.

Driver: Electronic Constant Current driver integrally mounted in fixture casing.

Dimming: Low Voltage dimming option (-DLV) works with standard Electronic Low Voltage Dimmers. Factory qualified for use with LUTRON Brand Dimmers: SELV-300P, VELV-300P, NELV-450 along with 3-Way versions. (-DLV) Dimming Option also compatible with Grafik Eye Dimming Interface ELVI-1000, smoothly dims down as low as 10% of initial light output with flicker-free operation. (-DUN) option is a universal dimming driver Uni-Dim™ that works with most ELV, incandescent and 0-10V fluorescent dimmers.

Lumen Maintenance: Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, heat sink design for maximum heat rejection to provide long LED life.

Warranty: Covered by a 5 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Finish: Available in All Black and Bright White/Black Heat Sink.

Beam Spread: Multifaceted glare reducing anodized reflector held in place with die-cast aluminum holder. Available in Flood, Narrow and Spot. Optical reflectors can be ordered separately. Use part #: RL-AP30-FL, RL-AP30-NF, RL-AP30-SP.

Color Temp: Available in 2700K, 3000K, 3500K and 4000K. LEDs binned to within 3-Step MacAdam Ellipses (SDCM) and surpasses the ANSI C78 377A standard for color deviation.

LED Details:

32W 2900 + Lumens Delivered

Color Rendering Index (CRI): 80

Lamp Equivalents: CMH-PAR20 39W, CMH-T4.5 39W

Benefit:

- Fully die-cast for high quality, long-lasting beauty
- 3 beam spread options for fine tuning footcandle distribution
- Powerful 2900 lumen output lights objects and spaces near and far
- T4 & T6 performance in a long life, cool running LED track head
- Available with Tool-less field changeable optics
- 0-10V, ELV or 3-Wire dimming options

FEATURE:




ORDERING EXAMPLE : LCD7430B-B25-T27

LCD7430	FINISH	BEAM SPREAD	DIMMING	COLOR TEMP	CRI
LCD7430	B :All Black	-B15 :Spot	Blank :120V Non-Dimming	-T27 :2700K	Blank :80 CRI
	W :Bright White/Black Heat Sink	-B25 :Narrow	UE-DUN :120V/277V ELV/2-Wire/0-10V Dimming	-T30 :3000K	-C90 :90 CRI*
		-B45 :Flood		-T35 :3500K	
				-T40 :4000K	
				-TWD :1850K-2700K	
				Warm Dimming	

* Special Order
Available with 277V input & Multi-Circuit Track. Consult Factory.

ID#: 3261

LCD7445 - APOLLO 50 CANOPY MOUNT - 4500 LUMEN LED TRACK HEAD



SPECIFICATION

120V 48W LED

Application: High Output architecturally-styled APOLLO LED Trackhead is perfect for applications where powerful lumen output is required. Fully die-cast with integrated heatsink, hardware and wiring for a sleek unobtrusive appearance. APOLLO combines long-lasting beauty and energy efficiency with intense lumen output. Excels at delivering maximum footcandles to objects, spaces and features from longer distances. Ideal for Retail and Commercial applications.

Mounting: Fixture includes a mounting bracket for installation directly to a 4" octagonal electrical junction-box.

Driver: Electronic Constant Current driver integrally mounted in fixture casing.

Dimming: Low Voltage dimming option (-DLV) works with standard Electronic Low Voltage Dimmers. Factory qualified for use with LUTRON Brand Dimmers: SELV-300P, VELV-300P, NELV-450 along with 3-Way versions. (-DLV) Dimming Option also compatible with Grafik Eye Dimming Interface ELVI-1000, smoothly dims down as low as 10% of initial light output with flicker-free operation. (-DUN) option is a universal dimming driver Uni-Dim™ that works with most ELV, incandescent and 0-10V fluorescent dimmers. DMX dimming option (-DMX) dims down to 0%. DMX in/out ports via RJ45 connector.

Lumen Maintenance: Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, heat sink design for maximum heat rejection to provide long LED life.

Warranty: Covered by a 5 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Finish: Available in All Black and Bright White/Black Heat Sink.

Beam Spread: Multifaceted glare reducing anodized reflector held in place with die-cast aluminum holder. Available in Flood, Narrow Flood and Spot. Optical reflectors can be ordered separately. Use part #: RL-AP50-FL, RL-AP50-NF, RL-AP50-SP.

Color Temp: Available in 2700K, 3000K, 3500K and 4000K. LEDs binned to within 3-Step MacAdam Ellipses (SDCM) and surpasses the ANSI C78 377A standard for color deviation.

LED Details:

48W 4500 + Lumens Delivered

Color Rendering Index (CRI): 80

Lamp Equivalents: 70W PAR38 , CMH-PAR30

Benefit:

- Fully die-cast for high quality, long-lasting beauty
- 3 beam spread options for fine tuning footcandle distribution
- Powerful 4500 lumen output lights objects and spaces near and far
- T4 & T6 performance in a long life, cool running LED track head
- Available with Tool-less field changeable optics
- 0-10V, ELV or 3-Wire dimming options

FEATURE:




ORDERING EXAMPLE : LCD7445B-B15-T27

LCD7445	FINISH	BEAM SPREAD	DIMMING	COLOR TEMP	CRI
LCD7445	B :All Black	-B15 :Spot	Blank :120V Non-Dimming	-T27 :2700K	Blank :80 CRI
	W :Bright White/Black Heat Sink	-B25 :Narrow Flood	UE-DUN :120V/277V ELV/2-Wire/0-10V Dimming	-T30 :3000K	-C90 :90 CRI*
		-B45 :Flood	UE-DMX :120V/277V DMX Dimming	-T35 :3500K	
				-T40 :4000K	

* Special Order
Available with 277V input & Multi-Circuit Track. Consult Factory.

ID#: 3262

LCD7460 - APOLLO 60 - 6000 LUMEN LED TRACK HEAD



SPECIFICATION

60W LED

Application: High Output architecturally-styled APOLLO LED Trackhead is perfect for applications where powerful lumen output is required. Fully die-cast with integrated heatsink, hardware and wiring for a sleek unobtrusive appearance. APOLLO combines long-lasting beauty and energy efficiency with intense lumen output. Excels at delivering maximum footcandles to objects, spaces and features from longer distances. Ideal for Retail and Commercial applications.

Connector: LITON track fixtures come standard with 3-Wire H-Type track connections. Fixture is factory preset for installation on single-circuit track. J-Type and L-Type connections are available with extended lead times - consult factory.

Driver: Electronic Constant Current driver integrally mounted in fixture casing.

Dimming: Low Voltage dimming option (-DLV) works with standard Electronic Low Voltage Dimmers. Factory qualified for use with LUTRON Brand Dimmers: SELV-300P, VELV-300P, NELV-450 along with 3-Way versions. (-DLV) Dimming Option also compatible with Grafik Eye Dimming Interface ELVI-1000, smoothly dims down as low as 10% of initial light output with flicker-free operation. (-DUN) option is a universal dimming driver Uni-Dim™ that works with most ELV, incandescent and 0-10V fluorescent dimmers. DMX dimming option (-DMX) dims down to 0%. DMX in/out ports via RJ45 connector.

Lumen Maintenance: Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, heat sink design for maximum heat rejection to provide long LED life.

Warranty: Covered by a 5 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Finish: Available in All Black and Bright White/Black Heat Sink.

Beam Spread: Multifaceted glare reducing anodized reflector held in place with die-cast aluminum holder. Available in Flood, Narrow Flood and Spot. Optical reflectors can be ordered separately. Use part #: RL-AP50-FL, RL-AP50-NF, RL-AP50-SP.

Color Temp: Available in 2700K, 3000K, 3500K and 4000K. LEDs binned to within 3-Step MacAdam Ellipses (SDCM) and surpasses the ANSI C78 377A standard for color deviation.

Label: cETL Listed

LED Details:

60W 6000 + Lumens Delivered

Color Rendering Index (CRI): 80

Lamp Equivalents: 70W CMH-T4.5 , 100W PAR38 CMH , PAR30 CMH

Benefit:

- Fully die-cast for high quality, long-lasting beauty
- 3 beam spread options for fine tuning footcandle distribution
- Powerful 6000 lumen output lights objects and spaces near and far
- T4 & T6 performance in a long life, cool running LED track head
- Available with Tool-less field changeable optics

FEATURE:



ORDERING EXAMPLE : LCD7460B-B15-T30

LCD7460	FINISH	BEAM SPREAD	DIMMING	COLOR TEMP	CRI
LCD7460	B :All Black	-B15 :Spot	Blank :120V Non-Dimming	-T27 :2700K	Blank :80 CRI
	W :Bright White/Black Heat Sink	-B25 :Narrow Flood	-UE-DUN :120V/277V/2-Wire/0-10V Dimming	-T30 :3000K	-C90 :90 CRI
		-B45 :Flood	-UE-DMX :120V/277V/DMX Dimming	-T35 :3500K	
				-T40 :4000K	

* Special Order



Product specifications subject to change without notice.
Tel: 323.904.0200 www.liton.com

