



LCMPD12RP : 12" LUMENPAD ROUND

LED DOWNLIGHT PENDANT MOUNT 2000LM (22W)



- 22W, 2000 Lumen Package
- Color Rendering Index: 90 CRI
- Lamp Equivalent: 65W BR30
- Super Slim 1" thick with die-cast aluminum frame
- Field-adjustable, 6' max. length Pendant
- 3-Year Warranty
- Black, Bronze, Silver and Matt Gold finishes available
- New 1000lm/3000lm Uplight option
- California Title 24/JA8 Compliant



ORDERING : LCMPD12RPW-LU13-TS30

LCMPD12RP

Fixture	Finish	Uplight	Dimming/Voltage	Color Temperature	Mounting
Finish²			Dimming/Voltage⁴		Mounting
All White	W		ELV-Dimming (120V) 2000lm	Blank³	Surface JBox Mount Blank
All Black	B		0-10V Dimming	UE-D10⁵	Track - 1 & 2-Circuit/1-Neutral -1C1N
Silver w/black cord	S		Color Temperature		Track - 2-Circuit/2-Neutral -2C2N
Bronze w/black cord	BZ				Track - 3-Circuit/1-Neutral -3C1N
Matt Gold w/black cord	G⁸				
Matt Gold w/white cord	GW⁸				
Uplight					
None	Blank				
1000lm (Up to 15W)	-LU10				
3000lm (Up to 35W)	-LU30				
			ColorSelect 2700K/3000K/3500K/4000K/5000K (90 CRI)	-TS27⁶	
				-TS30	
				-TS35	
				-TS40	
				-TS50⁶	
				-TS2750⁶	
			ColorSelect 3000K/3500K/4000K (90 CRI)	-TS354^{6,7}	

² Field paintable ring options available. Consult factory.
³ California Title 24/JA8 compliant with (Blank) ELV dimming (120V) only.
⁴ Requires 4" Octagon Electrical Box, 2-1/8" deep min. to install this luminaire.
⁵ Remote Emergency Battery Back Up Option only available for (UE-D10).
⁶ Not available for Uplight.
⁷ (-TS354) is not available with (UE-D10).
⁸ Special Order. Extended lead time.

SPECIFICATION

Application

The 12" LumenPad Round LED Downlight Pendant Mount floats with elegance in contemporary architectural applications, a unique combination of innovative, elegantly minimalist design and high-quality LED performance. The luminaire is perfect for Retrofit, New Construction and Remodel Applications in low to medium height ceilings. Super thin profile is unobtrusive in design and has low glare. Lens is a Polycarbonate Frosted White Lens.

Housing

Die-cast aluminum frame.

Mounting:

Universal mounting hardware allows mounting to all standard octagonal electrical junction boxes. White pendant mounting bracket and white field-adjustable cord for White finish. Black pendant mounting bracket and black field-adjustable cord for Black finish. Silver and Bronze finish come standard with Black pendant mounting bracket and black cord. Also available with the following Track Mounting: 1 & 2-Circuit/1-Neutral (-1C1N), 2-Circuit/2-Neutral (-2C2N), 3-Circuit/1-Neutral (-3C1N).

Lumen Maintenance:

Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Electrical Components

Thermal Management:

Effective thermal dissipation facilitated by integral heat sink design for maximum heat rejection to provide long LED life.

Temperature Rating:

Maximum temperature 90°C. Minimum temperature, -20°C.

Driver:

Standard dimming option smoothly dims down to 5% with standard Low Voltage dimmers. Works with standard electronic low voltage (ELV) dimmers. Factory qualified for use with Lutron brand dimmers: SELV300P, DVELV-300P, MAELV-600 and NELV-450. (UE-D10) 0-10V dimming option works with most 5-wire, 0-10V dimmers. Factory qualified for use with Leviton IP710-DLZ.

Color Temperature:

Available in 2700K, 3000K, 3500K, 4000K, 5000K, ColorSelect 2700K/3000K/3500K/4000K/5000K and ColorSelect 3000K/3500K/4000K, 90 CRI (Color Rendering Index). LED's binned according to ANSI C78 377A for color temperature and chromaticity ranges. For 2700K, special order, minimum order, extended led time may apply. Consult factory.

Finishes

High quality powder coat finish for maximum durability. Available in White, Black, Silver, Bronze and Matt Gold.

Certifications and Listings

ETL/cETL listed. Assembled in USA.


SPECIFICATION (Continued)

Caution	Fixtures must be grounded in accordance with national, state and/or local electrical codes. Failure to do so may result in serious personal injury.
Warranty	Covered by a 3-Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C. installations exceeding this temperature will result in reduced LED lamp life and avoided warranty.
Title 24/JA8 Compliant:	LCMPD12RP-T27 LCMPD12RP-T30 LCMPD12RP-T35 LCMPD12RP-T40 LCMPD12RP-TS354

PHOTOMETRY

LCMPD12RW-TS30 (2000lm, 22W, 3000K, CRI 90)


System Power:	22.5W	MULTIPLIERS	
Test Date:	10/2023	4000K	1.07
Beam Angle 50%:	112.7°	3500K	1.04
Field Angle 10%:	164.0°	3000K	1.00
Color Temperature:	3000K	2700K	0.99
CRI:	90		
Lumens Delivered:	1824.25		
CBCP:	633		
Power Factor:	0.99		



Height	Beam Diameter	FC
6.0'	18.0'	17.6
8.0'	24.0'	9.9
10.0'	30.0'	6.3
12.0'	36.1'	4.4
14.0'	42.1'	3.2

LCMPD12RW-TS40 (2000lm, 22W, 4000K, CRI 90)

System Power:	22.5W	MULTIPLIERS	
Test Date:	10/2023	4000K	1.00
Beam Angle 50%:	112.6°	3500K	0.97
Field Angle 10%:	164.1°	3000K	0.93
Color Temperature:	4000K	2700K	0.92
CRI:	90		
Lumens Delivered:	1960.3		
CBCP:	680		
Power Factor:	0.99		



Height	Beam Diameter	FC
6.0'	18.0'	18.9
8.0'	24.0'	10.6
10.0'	30.0'	6.8
12.0'	36.0'	4.7
14.0'	42.0'	3.5