



LCMPD7QP : 7" LUMENPAD SQUARE

LED DOWNLIGHT PENDANT MOUNT 1300LM (14W)



STEM H: 12", 18", 24", 36" and 48"
 *Stem Height is 96" Max Height and Field Cuttable to 2" Min.
 (other Custom Cuttable Heights available, consult Factory)



- Color Rendering Index: 90 CRI
- Lamp Equivalent: 65W BR30
- Super Slim, 1" thick with die-cast aluminum frame
- Field-adjustable, 6' max. length Pendant
- 3-Year Warranty
- Black, Bronze, Silver and Matt Gold finishes available
- California Title 24/JA8 Compliant

ORDERING : LCMPD7QPBZ-LU10-T30

LCMPD7QP

Fixture

Finish

Uplight

Dimming / Voltage

Color Temperature

Mounting

Finish¹

All White	W
All Black	B
Silver w/black cord	S⁶
Bronze w/black cord	BZ⁶
Matt Gold w/black cord	G⁷
Matt Gold w/white cord	GW⁷

Uplight

None	Blank
1300lm	-LU10

Dimming/Voltage³

ELV-Dimming (120V/277V)	Blank²
0-10V Dimming (120V/277V)	UE-D10⁴

Color Temperature

2700K (90 CRI)	-TS27⁵
3000K (90 CRI)	-TS30
3500K (90 CRI)	-TS35
4000K (90 CRI)	-TS40
5000K (90 CRI)	-TS50⁵
ColorSelect 2700K/3000K/ 3500K/4000K/ 5000K (90 CRI)	-TS2750⁵
ColorSelect 3000K/ 3500K/4000K (90 CRI)	-TS354⁵

Mounting

Surface JBox Mount	Blank
Track - 1 & 2-Circuit/1-Neutral	-1C1N
Track - 2-Circuit/2-Neutral	-2C2N
Track - 3-Circuit/1-Neutral	-3C1N
12" Stem Pendant	-STM12
18" Stem Pendant	-STM18
24" Stem Pendant	-STM24
36" Stem Pendant	-STM36
48" Stem Pendant	-STM48
96" to 2" Stem Pendant	-STM96ADJ*

¹ Field paintable ring options available. Consult factory.

² California Title 24/JA8 compliant with (Blank) ELV dimming (120V) only.

³ Requires 4" Octagon Electrical Box, 2-1/8" deep min. to install this luminaire.

⁴ Remote Emergency Battery Back Up Option only available for (UE-D10).

⁵ Not available for Uplight.

⁶ Silver and Bronze finish comes standard with Black pendant mounting bracket and cord.

⁷ Special Order. Extended lead time.

* Stem height is 96" max height and field cuttable to 2" min.
 (other custom cuttable heights available. Consult factory)

SPECIFICATION

Application

The 7" LumenPad Square LED Downlight Pendant Mount floats with elegance in contemporary architectural applications, a unique combination of innovative, elegantly minimalist design and high-quality LED performance. The luminaire is perfect for Retrofit, New Construction and Remodel Applications in low to medium height ceilings. Super thin profile is unobtrusive in design and has low glare. Lens is a Polycarbonate Frosted White Lens.

Housing

Die-cast aluminum frame. Optional (-PC) Non-Conductive Polycarbonate is available to minimize the risk of electrical shock from housing.

Mounting:

Universal mounting hardware allows mounting to all standard octagonal electrical junction boxes. White pendant mounting bracket and white field-adjustable cord for White finish. Black pendant mounting bracket and black field-adjustable cord for Black finish. Silver and Bronze finish come standard with Black pendant mounting bracket and black cord. Also available with the following Track Mounting: 1 & 2-Circuit/1-Neutral (-1C1N), 2-Circuit/2-Neutral (-2C2N), 3-Circuit/1-Neutral (-3C1N).

Lumen Maintenance:

Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Electrical Components

Thermal Management:

Effective thermal dissipation facilitated by integral heat sink design for maximum heat rejection to provide long LED life.

Temperature Rating:

Maximum temperature 85°C. Minimum temperature, -20°C.

Driver:

(Blank) Smoothly dims down to 5% with standard Low Voltage dimmers. Works with standard electronic low voltage (ELV) dimmers. Factory qualified for use with Lutron brand dimmers: SELV300P, DVELV-300P, MAELV-600 and NELV-450. (UE-D10) 0-10V dimming works with most 5-wire, 0-10V dimmers. Factory qualified for use with Leviton IP710-DLZ.

Color Temperature:

Available in 2700K, 3000K, 3500K, 4000K, 5000K, ColorSelect 2700K/3000K/3500K/4000K/5000K and ColorSelect 3000K/3500K/4000K, 90 CRI (Color Rendering Index). LED's binned according to ANSI C78 377A for color temperature and chromaticity ranges.

Finishes

High quality powder coat finish for maximum durability. Available in White, Black, Silver, Bronze and Matt Gold.

Certifications and Listings

ETL/cETL listed. Assembled in USA.


SPECIFICATION (Continued)

Caution	Fixtures must be grounded in accordance with national, state and/or local electrical codes. Failure to do so may result in serious personal injury.
Warranty	Covered by a 3-Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C. installations exceeding this temperature will result in reduced LED lamp life and avoided warranty.
Title 24/JA8 Compliant:	LCMPD7QP-T27 LCMPD7QP-T30 LCMPD7QP-T35 LCMPD7QP-T40 LCMPD7QP-TS354
Ready to Ship Items:	LCMPD7QPW-T-27 LCMPD7QPW-T-30 LCMPD7QPW-T-35 LCMPD7QPW-T-40

PHOTOMETRY

LCMPD7QW-TS50 (1300lm, 14W, 5000K, CRI 90)


System Power:	14W	MULTIPLIERS	
Test Date:	10/2023	2700K	0.90
Beam Angle 50%:	117.0°	3000K	0.92
Field Angle 10%:	169.6°	3500K	0.96
Color Temperature:	5207K	4000K	0.97
CRI:	93.6	5000K	1.00
Lumens Delivered:	1312		
CBCP:	425.8		
Power Factor:	0.92		



Height	Beam Diameter	FC
6.0'	19.58'	11.83
8.0'	26.11'	6.65
10.0'	32.64'	4.26
12.0'	39.16'	2.96
14.0'	45.69'	2.17

LCMPD7QWUE-D10-TS50 (1300lm, 14W, 5000K, CRI 90)

System Power:	14W	MULTIPLIERS	
Test Date:	10/2023	2700K	0.91
Beam Angle 50%:	117.2°	3000K	0.93
Field Angle 10%:	169.4°	3500K	0.97
Color Temperature:	5105K	4000K	0.99
CRI:	93.4	5000K	1.00
Lumens Delivered:	1384		
CBCP:	449.5		
Power Factor:	0.99		



Height	Beam Diameter	FC
6.0'	19.66'	12.49
8.0'	26.21'	7.02
10.0'	32.77'	4.50
12.0'	39.32'	3.12
14.0'	45.87'	2.29