


6" Architectural Housing (1-Lamp) w/ Self-Flanged Baffle Reflector

LFH6 SERIES - 6" HORIZONTAL CFL RECESSED LIGHTING



SPECIFICATION

Ceiling cut-out: 6 3/4"

Application: Architectural-grade recessed downlight housing for low to medium height ceilings and commercial installations. A variety of trims, compatible styles and finishes are available to achieve the proper décor and illumination.

Housing Frame: 16 gauge galvanized plaster ring with powder coat finish, six friction clips secure trim to housing for ceilings up to 1 3/4" thick. Triple slot bat-wing hanger brackets accommodate multiple bar hanger systems.

Mounting: Housing suitable for new construction installations only, Bat-Wing bar hanger brackets adjust vertically 3 1/4" for multiple ceiling types and accepts 1/2" EMT, 26" C-Channel Strut (C260) for T-bar ceilings and 27" linear hanger bars (L270) for wood joists. Heavy duty 16-gauge, die-formed galvanized steel. 1 1/4" maximum ceiling thickness.

Ballast: Electronic Class P 60Hz Ballast with Inherent thermal protection. For Double Twin Tube (DTT) or Triple Twin Tube Lamps (TTT). Sound A rated. Micro-Processor controlled. Min. starting temperature -10°C. Accessible from above or below the ceiling. Contact factory for detailed technical information on ballast specifications. Note: For dimming applications must use compatible dimmer switch. Consult specific ballast manufacturer for up-to-date compatibility list.

Socket Cap: Heavy-Duty steel socket enclosure with built-in ventilations. Die-cast aluminum fittings. Accepts compatible reflector trims.

Socket: Thermo-plastic socket UL Listed rated for high temperature and provides nickel plated contacts. Accepts 4-Pin lamps with electronic ballast selection.

Junction Box: 16 gauge pre-wired galvanized steel double Junction Box, 64 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (10) 3/4", (2) 1" and (8) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard die-cast aluminum fitting for flex-conduit.

Insulation Contact: Non-IC rated housing must be kept 3" from insulation.

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Emergency Option: Emergency back-up operates one lamp for a minimum of 90 minutes at 750 Lumens in case of power outage. Unit is remotely mounted. It includes battery, charger, and test switch with indicator light. Consult Factory for 1300 Lumen Package.

FEATURE:



Application: Architectural-grade recessed downlight reflector for medium to high ceilings in commercial and architectural installations. Reflector designed for minimal glare from lamp without sacrificing lumen output.


Construction: One piece self-flanged design enables a clean trim finish, without the need for a secondary trim ring. Heavy-gauge aluminum reflector prevents ugly dents during shipping and installation. Iridescent-free reflective coating minimizes unsightly rainbow effect.

Mounting: Pre-punched key holes allow mounting of socket cap assembly for housing, with vertically adjustable socket cap. Reflector held in place with 6 steel pressure springs mounted on housing frame.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship.

Label: UL Listed, cETL Listed

Assembled in USA



6" ARCHITECTURAL HOUSING

LFH6 CFL (1)42W/(2)26W Max

WATTAGE	BALLAST	OPTIONS
LFH6113 : (1) 13W	UE :120V/277V Electronic	Blank :None
LFH6113-126 : (1) 13W/18W/26W	UD :0-10V Dimming (120V/277V)	-EM :Emergency (Remote)
LFH6118 : (1) 18W	ADV-SM :120V/277V Smart Mate	-EMA :Emergency (Trim)
LFH6126 : (1) 26W	ADV-M7 :120V/277V Mark VII Dimming	-FS :Fuse
LFH6132 : (1) 32W	ADV-M10 :120V Mark X Dimming*	
LFH6142 : (1) 42W	ADV-M10-27 :277V Mark X Dimming**	
	LUT-HL :120V Lutron 3-Wire Dimming	
	LUT-TW :120V Tu-wire Dimming	
	LUT-HL-27 :277V Lutron 3-Wire Dimming	
	UE-347 :347V Electronic	
	E :120V Electronic	

* Not available for 13W option.
**18W only

SELF-FLANGED BAFFLE REFLECTOR

LR663 CFL (2) 26W DTT, (1) 42W TTT

Ordering example: LFH6132E/LR663WWF

BAFFLE / FINISH
LR663WWF :White Baffle/White Finish
LR663NNF :Natural Baffle/Natural Finish

6" Clear Reflector-Baffle (White)

Lamp: (2)CF26DD/E/841

Total Rated Lamp Lumens : 3600

Total Luminaire Efficiency : 28.9 %

CIE Type: Direct

Spacing Ratio: 1.30

Report File # LLI070307G.IES

By: Light Laboratory, Inc.

LM-63-2002

LUMINANCE DATA

6" Horizontal Housing : LFH6226UE

6" Reflector-Baffle : LR663W

32W Applications : LR653W

HOUSING		WATT.	LUMEN*	
1-LAMP	2-LAMP		1-LAMP	2-LAMP
LFH6113	LFH6213	13W	900	1800
LFH6118	LFH6218	18W	1200	2400
LFH6126UE	LFH6226	26W	1800	3600
LFH6132UE		32W	2400	

* Lumens may vary upon lamp types/manufacturers.

PROJECT INFORMATION

TYPE :

VOLTAGE :

PROJECT :


ITEM # :

DATE :

CANDLE POWER DISTRIBUTION

DEGREES
VERTICAL AVERAGE

0	466
1	462
3	467
5	472
7	490
9	508
11	521
13	534
15	542
17	542
20	533
23	507
26	481
29	443
33	395
38	346
43	293
48	230
55	98
65	44
75	20
85	4
90	0



LUMINANCE

Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	20742	20742	20742
55	9358	9358	9358
65	5702	5702	5702
75	4232	4232	4232
85	2514	2514	2514

MULTIPLIERS**


FINISHES		WATTAGES	
Black	0.85	13W	0.50
Natural	0.90	18W	0.66
Copper	0.85	32W	1.33
		42W	1.78

** Based on White Baffle (26W).

INITIAL FOOTCANDLES

(Beam angle : 102°)

Footcandles at center	Circle Diameter	Footcandles at edge
116.5	4.9	11.7
29.1	9.9	2.9
12.9	14.8	1.3
7.3	19.8	0.7
4.7	24.7	0.5
3.2	29.6	0.3
2.4	34.6	0.2
1.8	39.5	0.2
1.4	44.5	0.1
1.2	49.4	0.1



COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
0	34	34	34	34	34	34	34	34	32	32	32	31	31	31	29	29	29	29	29	29	29
1	32	31	30	29	31	30	29	28	29	28	27	28	27	27	27	26	26	26	25	25	25
2	30	28	26	24	29	27	25	24	26	25	24	25	24	23	24	23	23	22	22	22	22
3	27	25	23	21	27	24	22	21	23	22	20	23	21	20	22	21	20	19	19	19	19
4	25	22	20	18	25	22	20	18	21	19	18	21	19	18	20	19	18	17	17	17	17
5	23	20	18	16	23	20	18	16	19	17	16	19	17	16	18	17	16	15	15	15	15
6	22	18	16	14	21	18	16	14	18	16	14	17	15	14	17	15	14	13	13	13	13
7	20	17	15	13	20	17	14	13	16	14	13	16	14	13	15	14	13	12	12	12	12
8	19	15	13	12	19	15	13	12	15	13	12	15	13	12	14	13	11	11	11	11	11
9	18	14	12	11	17	14	12	11	14	12	11	14	12	11	13	12	10	10	10	10	10
10	17	13	11	10	16	13	11	10	13	11	10	13	11	10	12	11	10	9	9	9	9

ZONAL LUMEN SUMMARY

ZONE	LUMENS	%LAMP	%FIXT
0 - 30	398.75	11.10	38.30
0 - 40	611.32	17.00	58.80
0 - 60	925.76	25.70	89.00
0 - 90	1040.08	28.90	100.00
90 -120	0.00	0.00	0.00
90 -130	0.00	0.00	0.00
90 -150	0.00	0.00	0.00
90 -180	0.00	0.00	0.00
0 -180	1040.08	28.90	100.00