



Remodel w/ Micro Pinhole w/ Black Reflector

LH1299 SERIES - 2" LOW VOLTAGE RECESSED LIGHTING



SPECIFICATION

Ceiling cut-out: 2 5/8"

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired .05" baked enamel 1-piece drawn steel housing adjusts up to 1-1/4" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Trim is secured with torsion wing springs.

Mounting: Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

Transformer: Class 2 Noise-Free Electronic transformer installed adjacent to Junction Box, bottom and top accessible. Dimmable with dimmers designed for Electronic Low Voltage Loads. Thermally protected rated for 90° C.

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box: 16 gauge pre-wired aluminum Junction Box, suitable for through branch wiring for a maximum of (4) #12 AWG wires. Furnished with (2) 3/4" knock-outs. Screw-in or out covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Safety Labels: ETL/CETL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: cETL Listed

FEATURE:




Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.

Lens Inclusion: Clear glass protective safety lens included in packaging.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Accessories: Takes (1) 1 3/8" Media.

Label: cETL Listed



REMODEL LH1299R 12V Out MR11/MR16

OPTION	
LH1299R	:37W (120V)
LH1299R-50	:50W (120V)
LH1299R-50-27	:50W Max 277V input

MICRO PINHOLE W/ BLACK REFLECTOR LR1219 12V 35W Max MR11

TRIM FINISH	
LR1219W	:White Pinhole/Black Reflector
LR1219B	:Black Pinhole/Black Reflector
LR1219N	:Natural Metal Pinhole/Black Reflector
LR1219CO	:Copper Pinhole/Black Reflector
LR1219MO	:Mocha Pinhole/Black Reflector

Ordering example: LH1299R-50-27/LR1219CO