

Standard Remodel Housing w/ Metal Baffle w/ Brackets

LH5 SERIES - 5" LINE VOLTAGE RECESSED LIGHTING





SPECIFICATION

Ceiling cut-out: 5 1/2"

Application: General purpose recessed downlight housing for medium to high ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the proper décor and illumination.

Housing: Pre-wired housing adjusts up to $1\ 1/4''$ ceiling thickness. This housing has torsion remodeling clips for secure installation. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out (above ceiling access is not required).

Mounting: Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

Socket: Standard porcelain medium screw base socket with high temperature leads.

Junction Box: 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with 3/4", 1" and Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non IC rated housing must be kept 3" from insulation. IC rated housing rated for direct contact with low to medium density loosefill blown and rolled insulation. For use with high density loose fill blown insulation, reduce rated lamp wattage accordingly (roughly %15-%20).

Airflow: Airflight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: UL Listed, cETL Listed

FEATURE:






Application: Used for general ambient lighting. This traditional look of the baffle trim creates proper lighting that can be used in residential, retail, and light commercial applications.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Label: UL Listed, cETL Listed



STANDARD REMODEL HOUSING

LH5R 120V R30/PAR30/A19 MED E26

RATING WATTAGE VOLTAGE
LH5RICA:IC-Airtight Blank :75W Blank :120V

METAL	BAFFLE W/ BRACKETS
LR503	120V 75W Max R30/PAR30

BAFFLE FINISH	RING FINISH
LR503W : White	Blank :White
LR503B :Black	B :Black
LR503N :All Natural*	C :Chrome
	G :Gold
	N :Natural
	CO :Copper

 * Comes standard with a matching ring finish. Use "W" for White Ring.

ECMO GHTING GROUP

Ordering example: LH5RICA/LR503W

File Located online www.liton.com/spec