


Remodel Housing 120V/277V w/ Adjustable Pull Down LH7LV SERIES - 6" LOW VOLTAGE RECESSED LIGHTING



SPECIFICATION

Ceiling cut-out: 6 1/4"

Housing: Pre-wired housing adjusts up to 1 1/4" ceiling thickness. This housing has torsion remodeling clips for secure installation. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out (above ceiling access is not required).

Mounting: Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

Transformer: Class H insulated magnetic transformer installed adjacent to Junction Box, bottom and top accessible. Thermally protected rated for 90°C

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box : 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (7) 3/4" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non-IC rated housing must be kept 3" from insulation.

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: cETL Listed

FEATURE:



Application: These **adjustable** trims provide flexibility and versatility by doubling as both a downlight and as an accent light. Although most trims come with adjustable lamp holders, these trims have larger degrees of rotation resulting in both visual style and practical ergonomics.


The **elbow** design allows for full horizontal and vertical adjustability. With the lamp enclosed in the trim, annoying glares from back and sides of the trim are eliminated to provide visual comfort. Additional options are available providing glare and optical control.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Adjustability Lamp can be tilted 85° degrees vertically and rotated 358° degrees horizontally.

Accessories: Takes (1) 2" Media.

Label: cETL Listed



REMODEL HOUSING 120V/277V LH7RLV 12V 75W Max MR16 GU5.3

RATING	WATTAGE	VOLTAGE
LH7RLV :Standard	Blank :50W	Blank :120V/12V
	-75 :75W	-27 :277V/12V (Electronic*)

* Available with 120V/277V Magnetic Option, consult factory.

ADJUSTABLE PULL DOWN LR2697 12V 75W Max MR16

TRIM FINISH
LR2697W :White
LR2697B :Black
LR2697N :Natural
LR2697CO :Copper

Ordering example: LH7RLV/LR2697CO