


Standard E26 Housing w/ Gimbal Ring LH7 SERIES - 6" LINE VOLTAGE RECESSED LIGHTING



SPECIFICATION

Ceiling cut-out: 6 1/2"

Application: General purpose recessed downlight housing for medium to high ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the proper décor and illumination.

Housing: Pre-wired housing adjusts up to a 1 1/2" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs/standard coil springs or serrated clips.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Socket: Standard porcelain medium screw base socket with high temperature leads.

Junction Box : 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (7) 3/4" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non-IC rated housing must be kept 3" from insulation.

Airflow: Airtight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: UL Listed

FEATURE:




Application: The standard in residential adjustable illumination, these **gimbal** style trims provide flexibility and versatility from a single rotary axis. They double as both a downlight and as an accent light. They are an economic way to provide general and accent lighting with both vertical and horizontal aiming capabilities. Their large degrees of rotation result in both streamlined style and practical ergonomics. **PAR38** gimbals offer higher wattages accenting object far away objects.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Adjustability Lamp can be tilted 45° degrees vertically and rotated 358° degrees horizontally.

Label: UL Listed, cETL Listed

Limitation: Not for use w/Shallow Housings.



STANDARD E26 HOUSING LH7 120V 150W Max R30/PAR30/PAR38/A19 MED E26

RATING

LH7	:Standard
LH7A	:Airtight
LH7ICA	:IC-Airtight

GIMBAL RING LR340 120V/HID 150W Max PAR38

RING FINISH


LR340W	:White
LR340B	:Black
LR340G	:Gold
LR340N	:Natural
LR340CO	:Copper
LR340C	:Chrome

Ordering example: LH7/LR340CO

Type :

Project :

Catalog # :



D : Distance to the horizontal or vertical surface.
 FC : Initial foot candles at the center of the beam.
 L : Length of the beam where candle power is reduced to 50% of center beam candle power.
 W : Width of the beam where candle power is reduced to 50% of center beam candle power.
 CB : Distance to the center of the beam.

Lamp data given is typical and is based on bare lamp performance. Contact lamp manufacturers for availability and specific performance. Distance, length, and width given in decimal feet.

PAR38 Halogen E26 Medium Base



	0° Aiming Angle Horizontal Foot candles				30° Aiming Angle Horizontal Foot candles					30° Aiming Angle Vertical Foot candles					45° Aiming Angle Vertical Foot candles				
	D	FC	L	W	D	FC	L	W	CB	D	FC	L	W	CB	D	FC	L	W	CB
45W PAR / CAP / SPL / SP9 Beam Spread = 9° CBCP = 10,000 Rated Life = 2,500 Hrs.	6	278	2.2	2.2	3	275	2.2	1.9	1.7	2	206	4.6	2.2	3.5	3	183	3.2	2.3	3.0
	8	156	2.6	2.6	4	155	2.8	2.4	2.3	3	92	6.6	3.1	5.2	4	103	4.1	2.9	4.0
	10	100	3.1	3.1	5	99	3.4	3.0	2.9	4	52	8.7	3.9	6.9	5	66	5.1	3.5	5.0
	12	69	3.5	3.5	6	69	4.0	3.5	3.5	5	33	10.8	4.8	8.7	6	46	6.0	4.2	6.0
45W PAR / CAP / SPL / FL30 Beam Spread = 30° CBCP = 1,500 Rated Life = 2,500 Hrs.	3	167	2.0	2.0	3	208	2.6	2.3	1.7	2	156	5.9	2.5	3.5	3	139	3.9	2.7	3.0
	4	64	2.5	2.5	4	117	3.3	2.9	2.3	3	69	8.6	3.6	5.2	4	78	5.0	3.4	4.0
	5	60	3.1	3.1	5	75	4.1	3.5	2.9	4	39	11.3	4.7	6.9	5	50	6.2	4.2	5.0
	6	42	3.6	3.6	6	52	4.8	4.1	3.5	5	25	14.1	5.8	8.7	6	35	7.3	4.9	6.0
45W PAR / CAP / SPL / WFL50 Beam Spread = 50° CBCP = 700 Rated Life = 2,500 Hrs.	2	175	1.8	1.8	8	260	2.1	1.8	4.6	5	222	3.6	2.0	8.7	7	227	2.6	2.0	7.0
	3	78	2.3	2.3	11	138	2.7	2.4	6.4	6	154	4.2	2.3	10.4	9	137	3.2	2.4	9.0
	4	44	2.8	2.8	14	85	3.3	2.9	8.1	7	113	4.9	2.6	12.1	11	92	3.9	2.8	11.0
	5	28	3.2	3.2	17	58	4.0	3.5	9.8	8	87	5.5	2.9	13.9	13	66	4.5	3.3	13.0
60W PAR / CAP / SPL / SP9 Beam Spread = 9° CBCP = 16,000 Rated Life = 3,000 Hrs.	8	250	2.5	2.5	3	292	2.6	2.3	1.7	2	219	5.9	2.5	3.5	3	194	3.9	2.7	3.0
	11	132	3.6	3.6	4	164	3.3	2.9	2.3	3	97	8.6	3.6	5.2	4	109	5.0	3.4	4.0
	14	82	4.7	4.7	5	105	4.1	3.5	2.9	4	55	11.3	4.7	6.9	5	70	6.2	4.2	5.0
	17	55	5.8	5.8	6	73	4.8	4.1	3.5	5	35	14.1	5.8	8.7	6	49	7.3	4.9	6.0
60W PAR / CAP / SPL / NFL25 Beam Spread = 25° CBCP = 3,300 Rated Life = 3,000 Hrs.	4	206	2.5	2.5	4	216	3.3	2.9	2.3	2	288	5.9	2.5	3.5	3	256	3.9	2.7	3.0
	5	132	3.1	3.1	5	138	4.1	3.5	2.9	3	128	8.6	3.6	5.2	4	144	5.0	3.4	4.0
	6	92	3.6	3.6	6	96	4.8	4.1	3.5	4	72	11.3	4.7	6.9	5	92	6.2	4.2	5.0
	7	67	4.1	4.1	7	70	5.5	4.7	4.0	5	46	14.1	5.8	8.7	6	64	7.3	4.9	6.0
60W PAR / CAP / SPL / FL30 Beam Spread = 30° CBCP = 2,500 Rated Life = 3,000 Hrs.	3	278	3.5	3.5	3	167	5.0	4.0	1.7	2	125	44.9	4.6	3.5	2	250	6.1	3.3	2.0
	4	156	4.6	4.6	4	94	6.5	5.2	2.3	3	56	67.2	6.6	5.2	3	111	9.0	4.8	3.0
	5	100	5.6	5.6	5	60	8.0	6.4	2.9	4	31	89.5	8.7	6.9	4	63	11.8	6.3	4.0
	6	69	6.6	6.6	6	42	9.6	7.6	3.5	5	20	112.0	10.8	8.7	5	40	14.7	7.8	5.0
90W PAR / CAP / SPL / SP9 Beam Spread = 9° CBCP = 22,000 Rated Life = 2,500 Hrs.	9	274	2.7	2.7	11	288	3.0	2.6	4.6	7	237	5.4	2.8	12.1	9	287	3.6	2.6	9.0
	12	154	3.5	3.5	15	155	3.9	3.4	8.7	9	144	6.8	3.5	15.6	13	138	5.0	3.6	13.0
	15	99	4.4	4.4	19	97	4.8	4.2	11.0	11	96	8.3	4.2	19.1	17	80	6.4	4.6	17.0
	18	69	5.3	5.6	23	66	5.8	5.0	13.3	13	69	9.7	4.9	22.5	21	53	7.8	5.6	21.0
90W PAR / CAP / SPL / FL30 Beam Spread = 30° CBCP = 3,500 Rated Life = 2,500 Hrs.	4	219	3.6	3.6	5	270	4.1	3.5	2.9	3	250	8.6	3.6	5.2	4	281	5.0	3.4	4.0
	6	97	4.7	4.7	7	138	5.5	4.7	4.0	4	141	11.3	4.7	6.9	5	180	6.2	4.2	5.0
	8	55	5.8	5.8	8	83	7.0	6.0	5.2	5	90	14.1	5.8	8.7	6	125	7.3	4.9	6.0
	10	35	6.8	6.8	11	56	8.4	7.2	6.4	6	63	16.8	6.8	10.4	7	92	8.5	5.7	7.0
120W PAR / CAP / SPL / FL30 Beam Spread = 30° CBCP = 4,600 Rated Life = 3,000 Hrs.	4	288	1.3	1.3	4	469	1.2	1.1	2.3	3	278	2.3	1.3	5.2	5	200	2.0	1.5	5.0
	5	184	1.7	1.7	6	208	1.7	1.5	3.5	4	156	3.0	1.7	6.9	6	139	2.3	1.7	6.0
	6	128	2.0	2.0	8	117	2.1	1.8	4.6	5	100	3.6	2.0	8.7	7	102	2.6	2.0	7.0
	7	94	2.3	2.3	10	75	2.5	2.2	5.8	6	69	4.2	2.3	10.4	8	78	2.9	2.2	8.0
120W PAR / CAP / SPL / WFL50 Beam Spread = 50° CBCP = 2,000 Rated Life = 3,000 Hrs.	3	222	2.0	2.0	2	281	1.9	1.6	1.2	2	64	5.9	2.5	3.5	2	188	2.7	1.9	2.0
	4	125	2.5	2.5	3	125	2.6	2.3	1.7	3	42	8.6	3.6	5.2	3	83	3.9	2.7	3.0
	5	80	3.1	3.1	4	70	3.3	2.9	2.3	4	23	11.3	4.7	6.9	4	47	5.0	3.4	4.0
	6	56	3.6	3.6	5	45	4.1	3.5	2.9	5	15	14.1	5.8	8.7	5	30	6.2	4.2	5.0
250W PAR / CAP / SPL / SP10 Beam Spread = 10° CBCP = 46,500 Rated Life = 4,500 Hrs.	13	275	2.3	2.3	2	131	3.1	2.5	1.2	1	175	11.1	2.3	1.7	2	88	5.2	3.0	2.0
	18	144	3.2	3.2	3	58	4.4	3.6	1.7	2	44	21.9	4.1	3.5	3	39	7.5	4.4	3.0
	23	88	4.1	4.1	4	33	5.8	4.7	2.3	3	19	32.6	6.0	5.2	4	22	9.9	5.7	4.0
	28	59	5.1	5.1	5	21	7.1	5.8	2.9	4	11	43.3	7.9	6.9	5	14	12.3	7.0	5.0
250W PAR / CAP / SPL / FL30 Beam Spread = 30° CBCP = 9,000 Rated Life = 4,500 Hrs.	6	250	1.7	1.7	7	245	1.9	1.7	4.0	4	250	3.0	1.7	6.9	6	222	2.3	1.7	6.0
	8	141	2.1	2.1	9	148	2.3	2.0	5.2	5	160	3.6	2.0	8.7	8	125	2.9	2.2	8.0
	10	90	2.6	2.6	11	99	2.7	2.4	6.4	6	11	4.2	2.3	10.4	10	80	3.6	2.6	10.0
	12	63	3.1	3.1	13	71	3.1	2.8	7.5	7	82	4.9	2.6	12.1	12	56	4.2	3.1	12.0