


Remodel w/ Adjustable Gimbal 4" H.I.D (MR16)



SPECIFICATION

Ceiling cut-out: 4 1/4"

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired housing adjusts up to 1 1/4" ceiling thickness. This housing has torsion remodeling clips for secure installation. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs/standard coil springs. Designed to be installed in existing sheet rock ceilings via ceiling cut out (above ceiling access is not required).

Mounting: Housing suitable for existing or new construction installations, supplied with high tension remodeling clips, designed to secure the housing to an existing sheetrock ceiling for fast and easy installation.

Socket: Pulse-Rated 4KV, porcelain Twist and Lock GX10 socket with high temperature leads and nickel-plated contacts.

Ballast: High Power Factor electronic 120V 60Hz ballast. Provides up to 15% energy savings versus magnetic and increased lamp life. Lightweight design with safety "Auto Turn-off Function". Class A sound rating. Thermal and transient protection. Excellent line regulation of $\pm 0.5\%$ output variation. Min. starting temperature $-15^{\circ}\text{C}/+5^{\circ}\text{F}$. THD less than 15%.

Junction Box: 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (6) 3/4" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non-IC rated housing must be kept 3" from insulation.

Safety Labels: ETL/CETL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: cETL Listed

FEATURE:



Application: These **adjustable** fixtures provide flexibility and versatility by doubling as both a downlight and as an accent light. These trims come with adjustable lamp holders and have larger degrees of rotation resulting in both visual style and practical ergonomics.

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.


Lens Inclusion: Clear glass protective safety lens included in packaging.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Adjustability Lamp can be tilted 35° degrees vertically.

Accessories: Takes up to (3) 2" Media.

Label: UL Listed, cETL Listed



REMODEL LH99MHR-GX10

HID 20W/39W MR16 GX10

ADJUSTABLE GIMBAL

LR1409 12V/120V/HID 75W Max MR16

WATTAGE	VOLTAGE
LH99MHR-GX10-20 :20W	Blank :120V
LH99MHR-GX10-39 :39W	-27 :277V

FINISH
LR1409W :White
LR1409B :Black
LR1409N :Natural
LR1409CO :All Copper

* Comes standard with a matching ring finish. Use "W" for White Ring.

Ordering example: LH99MHR-GX10-20/LR1409N