


TYPE CATALOG#

## Deep CFL Housing w/ Fresnel Lens w/ Reflector LH99P SERIES - 4" COMPACT FLUORESCENT RECESSED LIGHTING





## **SPECIFICATION**

Ceiling cut-out: 4 1/2"

**Application:** An excellent choice to illuminate a shower or bath. These trims produce a strong vibrant light that fully illuminates the shower and bath areas without drawing attention to the source. These trims figture a clear reflector allowing greater illumination without increasing the lamp wattage.

**Application:** General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.

**Housing:** Pre-wired housing adjusts up to a  $1\ 1/4''$  ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Trim is secured with torsion wing springs.

**Mounting:** Steel pressure springs mounted on trim to ensure positive retention inside housing.

**Mounting:** Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Label: UL Listed, cETL Listed

**FEATURE:** 

**Ballast:** Electronic Class P 60Hz Ballast with Inherent thermal protection. For Double Twin Tube (DTT) or Triple Twin Tube Lamps (TTT). Sound A rated. Micro-Processor controlled. Min. starting temperature -10°C. Accessible from above or below the ceiling. Contact factory for detailed technical information on ballast specifications. Note: For dimming applications must use compatible dimmer switch. Consult specific ballast manufacturer for up-to-date compatibility list.

**Socket:** Thermo-plastic socket UL Listed rated for high temperature and provides nickel plated contacts. Accepts 4-Pin lamps with electronic ballast selection.


**Junction Box** :16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (7) 3/4" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

**Insulation Contact:** Non-IC rated housing must be kept 3" from insulation.

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

**Emergency Option:** Emergency back-up operates one lamp for a minimum of 90 minutes at 750 Lumens in case of power outage. Unit is remotely mounted. It includes battery, charger, and test switch with indicator light. Consult Factory for 1300 Lumen Package.

Label: cETL Listed



## DEEP CFL HOUSING

LH99P CFL 13W DTT, 26W TTT

WATTAGE + BALLAST			OPTIONS		
LH99PE	:13W 120V	Blank	:None		
LH99PUD	:13W 120V/277V 0-10V Dimming	-27	:120V/277V		
LH99P-18E	:18W 120V	-EM	:Emergency		
LH99P-18UD	:18W 120V/277V 0-10V Dimming				
LH99P-26E	:26W 120V				
LH99P-26UD	:26W 120V/277V 0-10V Dimming				
* 277V Not available for 13W Magnetic.					

## FRESNEL LENS W/ REFLECTOR

**LRS923** 120V/CFL 40W Max A19, 50W PAR20

REFLECTOR FINISH	RING FINISH		RATING	
LRS923 :Clear	PW	:White (Plastic)	Blank	:Damp Location
	W	:White	-WL	:Wet Location
	В	:Black		
	C	:Chrome		
	G	:Gold		
	N	:Natural		
	CO	:Copper		

Ordering example: LH99P-26E-EM/LRS923W

