



LHFRLD6C - 6" C-SERIES

(COB) CHIP ON BOARD BEAM CONTROL LED
IC FIRE-RATED DOWNLIGHT, 1000LM-2000LM (10W-20W)

- Patented dual-layer housing with one-hour fire rating
- IC Rated and Airtight
- Heavy Duty Self-Flanged Reflector
- Soft Even Lumen Distribution



Ceiling Cut-out: 6-3/8"
Ceiling Thickness: 1" Max



ORDERING : LHFRLD6C-DIN-EM/CR6LC40SW-B20-T27

LHFRLD6C							
Housing	Driver Options	Emergency Options	/	Reflector Finish	Beam Spread	CCT	
Housing ¹		Emergency Options		Reflector Finish		Beam Spread	
1000lm (10W)	LHFRLD6C10	None	Blank	Satin Haze Reflector/	/CR6LC40SW	20° Spot	-B20
1300lm (15W)	LHFRLD6C15	12W Emerg. Back-Up	-EM³	White Ring		30° Narrow Flood	-B30
2000lm (20W)	LHFRLD6C20	Remote Locator	-EMAC³	White Reflector/	/CR6LC40WW	40° Flood	-B40
		Emergency System		White Ring		60° Wide Flood	-B60
		Generator Transfer	-GTD	All Black	/CR6LC40BB	75° Very Wide Flood	-B75
		Device		Clear Specular	/CR6LC40CW		
				Reflector/White Ring			
				All Satin Haze	/CR6LC40SS		
Driver Options ²						CCT	
0-10V Dimming	UE-D10					2700K (90 CRI)	-T27
UniDim™ 0-10V ELV and Triac Dimming	UE-DUN					2700K (97 CRI)	-T27-C97
120V ELV and Triac Dimming	-DIN					3000K (90 CRI)	-T30
Lutron HighLume	UE-DHL					3000K (97 CRI)	-T30-C97
Lutron EcoSystem	UE-ECO					3500K (90 CRI)	-T35
347V	-347⁴					4000K (90 CRI)	-T40
0-10V Dimming (1%)	UE-D10P1					5000K (80 CRI)	-T50

¹ Housing must match corresponding reflector in column to right.

² All drivers are 120V/277V unless otherwise noted.

³ Access above ceiling required for -EM and -EMAC

⁴ -347 is not available for LHFRLD6C10

COMPATABILITY


VR800

Round Vandal Resistant Kit for 8"



P-CR672SW

Wall Wash for 6"



P-CR671W

6" Wall Wash
CR6 Accessory



CR6-GSKT

6" Commercial
Self-Adhesive Gasket



SPECIFICATION

Applications

Professional-grade IC fire-rated recessed LED downlight for medium to high ceilings in commercial and architectural spaces.

Fire Rating

Stops the progress of an active fire. Meets the fire-stop capabilities of a typical 5/8" gypsum board (drywall) barrier. Eliminates the requirement to specify more expensive fire-rated materials or the use of manually constructed drywall enclosures.

Patented dual-layer housing is constructed of 20-gauge aluminum designed to maintain the continuity of fire-rated ceiling assemblies, subject to UL classified L500 series fire rated assemblies rated for 1-hour. UL Certifications and Approvals for One-Hour Fire Rating: UL263, CAN/ULC S101-07, ASTM E119-00A, UBC7-1, NFPA 251 and ASI A2.1 under U.S. Patent.

Mounting

Housing suitable for new construction installations. Adjusts up to 1-1/4" ceiling thickness. Supplied with (2) 24" adjustable hanger bars. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Trim is secured via positive retention friction clips.

Driver

120V/277V AC 50/60Hz Electronic Direct Current Class 2 driver integrally mounted on large access Junction Box. Power Factor > 0.90. Operating Temperature: -10°C to +80°C. Accessible from above or below ceiling. (UE-D10) 0-10V dimming works with most 5-wire, 0-10V dimmers. Factory qualified for use with Leviton IP710-DLZ.

(UE-DUN) Uni-Dim™ dimming option is a universal dimming system that works with most 120V, 3-wire ELV, 2-wire incandescent, and 120V/277V, 5-wire 0-10V fluorescent dimmers.

Emergency Options

Emergency LED Battery Back-up available, remotely mounted adjacent to housing by installer. When AC power fails, the device immediately switches to the emergency mode, operating the LEDs for a minimum of 90 minutes. Remote test switch, and plate cover included. Optional Generator Transfer Device switches the driver to auxiliary generator power during the loss of normal AC power, (recommended for applications requiring individual circuit switching).

Color Temperature

Available in 2700K, 3000K, 3500K, 4000K and 5000K.

Insulation Contact

IC rated for direct insulation contact.

Thermal Management

Heat dissipation facilitated by the exposed integral aluminum heat sink to maximize heat rejection in an open-air environment. The recommended ambient temperature should be below 35°C to achieve a minimum L70 life of 50,000 hours according to the LM80 standard.

Reflector

One piece, self-flanged dual-reflector LED design enables a clean trim finish, without the need for a secondary trim ring. Heavy-gauge aluminum reflector prevents ugly dents during shipping and installation. Deeply mounted LED provides 50 degree visual cutoff for a glare-free appearance. Satin Haze reflector/White flange.

Reflector Finish

Available in Haze Reflector/White Ring White Reflector/White Ring, All Black, Clear Specular Reflector/White., and All Satin Haze.

Power Connection

LED lamp array is replaceable via on board quick disconnect terminal. Meets CA Title 24 Requirements and other standards restricting the use of Medium Base or Bi-Pin Sockets.

Lumen Maintenance

Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Junction Box

16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (6) 1/2", and (2) 3/4" knock-outs. Strain clamps to install or remove covers for easy access and ground wire.

Airflow

Airtight reflector design is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute).

Caution

LITON recommends use of surge protectors on the power entering LED Housings. Surge damage is not covered by warranty. (+1KV). Fixtures must be grounded in accordance with national, state and/or local electrical codes. Failure to do so may result in serious personal injury.

Certifications and Listings

UL/cUL listed to UL1598 and UL8750. Suitable for dry, damp and wet locations. NYC approved: Calendar #41937. STC (Sound Transmission Class), and IIC (Impact Insulation Class) compliant.

Warranty

Covered by a 5-Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.