


4" LED Housing (700lm/1000lm) w/ 4" Adjustable Reflector (700lm) 4" LED



SPECIFICATION

Ceiling cut-out: Ceiling Cut-out: 3 7/8"

Application: This miniature General Purpose LED housing is perfect for low to medium height ceilings in residential and light commercial applications. Its small aperture makes it ideal for strategic placement where space is limited and energy savings is important. A variety of trim styles, finishes, and beam spreads are available to achieve a desired look.

Housing: Pre-wired housing adjusts up to a 1 1/4" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Trim is secured via positive retention friction clips.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Power Connection: LED heat sinked lamp module is replaceable via onboard quick exclusionary disconnect terminal. No tools required. Meets CA Title 24 Requirements and other standards restricting the use of Medium Base or Bi-Pin Sockets.

Driver: Electronic Direct Current U.L. Listed driver mounted away from LED Array for cool operation and end-of-life modularity. Comes standard with 120VAC input and available with optional 120V/277V universal voltage input. Consult factor.

Dimming: Standard dimming option smoothly dims down as low as 10% of initial light output with flicker-free operation works with standard Incandescent dimmers. Factory qualified for use with LUTRON Brand Dimmers: S600PR, DVSCCL-153P & DV600PR as well as Leviton# IP106-600V. Also dims with Electronic Low Voltage dimmers. Factory qualified for use with LUTRON Brand Dimmers: SELV-300P, DVELV-300P, NELV-450 along with 3-Way versions. "-DUN" Universal Dimming Option dims with above mention dimming controls along with standard 0-10V dimming signals.

Emergency Options: Emergency LED Battery Back-up available, remotely mounted adjacent to housing by installer. When AC power fails, the device immediately switches to the emergency mode, operating the LEDs for a minimum of 90 minutes. Remote test switch and plate cover included. Optional Generator Transfer Device switches the driver to auxiliary generator power during the loss of normal AC power, (recommended for applications requiring individual circuit switching).

Junction Box : 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (7) 3/4" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Safety Labels: ETL/CETL listed. Suitable for damp locations. NYC approved: Calendar #41937.

FEATURE:




Application: Used in both general and accent lighting applications. Utilizing the crisp, light output and the precision aiming capabilities of the MR16 lamps, this trim brings out the most vibrant colors from artwork and accentuates the beauty of jewelry, crystals as well as architectural features. Provides an even illumination with excellent lumen cutoff to create a dramatic lighting scene. The highly reflective surface allows for maximum lumen output.

Power Connection: LED heat sinked lamp module is replaceable via onboard quick exclusionary disconnect terminal. No tools required. Meets CA Title 24 Requirements and other standards restricting the use of Medium Base or Bi-Pin Sockets.

Lumen Maintenance: Minimum 35,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, finned heat sink design for maximum heat rejection to provide long LED life.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.



4" LED HOUSING (700LM/1000LM) LHLD49C20 10W/13W LED

DIMMING	HOUSING OPTIONS	OPTIONS
LHLD49C20 :120V ELV/Triac Dimming	Blank :None	Blank :None
LHLD49C20UE-DUN :120V-277V 0-10V/ELV/Triac Dimming	-CHP :Chicago Plenum	-EM :Emergency Backup*

* Above ceiling access required for EM option.

4" ADJUSTABLE REFLECTOR (700LM) LRLD1471 10W LED

FINISH	BEAM SPREAD	COLOR TEMP
LRLD1471W :All White	-B45:Flood	Blank :3000K (90CRI)
LRLD1471BB :All Black	-B60:Wide Flood	-T27 :2700K (90CRI)
LRLD1471N :All Natural		-T35 :3500K (90CRI)
LRLD1471BN :Black Reflector/Natural Ring		-T40 :4000K (90CRI)
LRLD1471C :Clear Reflector/White Ring		
LRLD1471SN :Satin Reflector/Natural Ring		

Ordering example: LHLD49C20/LRLD1471W-B45