


LREBLD5678 - 5" & 6" LED ADJUSTABLE GIMBAL

5" & 6" LED



SPECIFICATION

120V AC LED 12W

Application: This Adjustable Gimbal LED Retrofit Trim provides directional adjustability allowing it to function as both a downlight and an accent light. Fits most 5" and 6" line voltage recessed housings with Orange Push-In Quick Connector Base. Perfect for Retrofit, New Construction and Remodel Applications.

Mounting: Mounts into standard 5 & 6" General Purpose Recessed housing with steel pressure springs mounted on trim to ensure positive retention inside housing. Alternate mounting methods available, consult factory.

Power Connection: Comes standard with socket mounted to top of fixture. Meets CA Title 24 Requirements and other standards restricting the use of Medium Base or Bi-Pin Sockets.

Lumen Maintenance: Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, finned heat sink design for maximum heat rejection to provide long LED life.

Driver: Electronic Direct Current driver mounted on fixture.

Dimming: 'L-DIN' dimming option smoothly dims down to 5% of initial light output with flicker-free performance. Works with standard incandescent dimmers. Factory qualified for use with Lutron brand dimmers: S600PR, DVSCCL-153P & DV600PR as well as Leviton IP106-600W. Works with standard electronic low voltage (ELV) dimmers. Factory qualified for use with Lutron brand dimmers: SELV300P, DVELV-300P, MAELV-600 and NELV-450.

Safety Labels: ETL/CETL listed. UL listed for wet locations. NYC approved: Calendar#41937. High Efficacy Luminaire Certified by the California Energy Commission (CEC) as Title 24 / JA8 Compliant.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Adapter: Available in and Med Base. Binned according to ANSIC78 377A for color temperature and chromaticity ranges. Consult factory as extended lead times and minimum order quantities apply.

COMPATIBILITY

 LH7ICA-QC NEW CONSTRUCTION (2-PIN)	 LH7RICA-QC REMODEL HOUSING (2-PIN)	 LH27 STANDARD SHALLOW E26 HOUSING
 LH5 STANDARD NEW CONSTRUCTION HOUSING	 LH5R STANDARD REMODEL HOUSING	 LSHFR7-QC 6" IC 2HR FIRE-RATED LED HOUSING (SHALLOW)

Note: Wattage limitations on compatible items must be met.

LED Details:

12W 900 Lumen Package
Color Rendering Index (CRI)²: 90
Color Temperature: 3,000K
Lamp Equivalent: 75W R30

Benefit:

- Adjustable, functions as downlight and accent.
- 12W, 900Lm trim fits most 5" & 6" Housings
- Die cast for long lasting durability
- Quick Ship Item
- 90 CRI Standard

Title 24/JA8 Compliant

- LREBLD5678_-T27
- LREBLD5678_-T30
- LREBLD5678_-T40

FEATURE:



ORDERING EXAMPLE : LREBLD5678W-T27

LREBLD5678	FINISH	COLOR TEMP	ADAPTER
LREBLD5678	W :White Reflector/White Ring	-T27 :2700K	Blank :None
	B :Black Reflector/Black Ring	-T30 :3000K	/SQG4-MED :Med Base