


LREBLDQ5602 - 5" & 6" SQUARE LED (1100LM) 5" & 6" LED



SPECIFICATION

120VAC 16W

Application: 6" General Purpose LED Trim with Orange Push-In Quick Connector Base is perfect for Retrofit, New Construction and Remodel Applications in low to medium height ceilings.

Mounting: Mounts into standard 5 & 6" General Purpose Recessed housing with steel pressure springs mounted on trim to ensure positive retention inside housing. Alternate mounting methods available, consult factory.

Power Connection: Comes standard with socket mounted to top of fixture. Meets CA Title 24 Requirements and other standards restricting the use of Medium Base or Bi-Pin Sockets.

Lumen Maintenance: Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, finned heat sink design for maximum heat rejection to provide long LED life.

Driver: Electronic Direct Current driver mounted on fixture.

Dimming: 'L-DIN' dimming option smoothly dims down to 5% of initial light output with flicker-free performance. Works with standard incandescent dimmers. Factory qualified for use with Lutron brand dimmers: S600PR, DVSCCL-153P & DV600PR as well as Leviton IP106-600W. Works with standard electronic low voltage (ELV) dimmers. Factory qualified for use with Lutron brand dimmers: SELV300P, DVELV-300P, MAELV-600 and NELV-450.

Safety Labels: ETL/CETL listed. UL listed for wet locations. NYC approved: Calendar#41937.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Finish: Only available in White Reflector/White Ring.

Color Temp: Available in 2700K*, 3000K, 3500K* and 4000K*.

COMPATIBILITY

 LH7 STANDARD E26 HOUSING	 LH7RICA REMODEL E26 HOUSING	 LH27 STANDARD SHALLOW E26 HOUSING
 LH7ICA-QC NEW CONSTRUCTION (2-PIN)	 LH7RICA-QC REMODEL HOUSING (2-PIN)	 LSHFR7-QC 6" IC 2HR FIRE-RATED LED HOUSING (SHALLOW)

Note: Wattage limitations on compatible items must be met.

LED Details:

16W 1100 Lumen Package

Color Rendering Index (CRI): 90
Color Temperature: 3,000K
Lamp Equivalent: 75W R30

Benefit:

- Full Die-Cast Construction
- 16 watt trim fits standard 5" and 6" housings
- Fully die-cast for long lasting durability
- Trims are UL listed for wet locations
- 90 CRI Standard

FEATURE:

ORDERING EXAMPLE : LREBLDQ5602W-T27/SG24-MED

LREBLDQ5602	FINISH	COLOR TEMP	ADAPTER OPTION
LREBLDQ5602	W :White Reflector/White Ring	-T27 :2700K* -T30 :3000K -T35 :3500K* -T40 :4000K*	Blank :None /SQG4-MED :Med Base

* Special Order Item. Consult factory for stock.