


LRLD4 - 4" LED REFLECTOR

4" LED GU24



SPECIFICATION

120V LED / GU24

Application: General Purpose LED Trim for Retrofit, New Construction and Remodel Applications in low to medium height ceilings. Qualified as high efficacy for Title 24 by the California Energy Commission.

Mounting: Mounts into standard 6" General Purpose Recessed housing with steel pressure springs mounted on trim to ensure positive retention inside housing.

Lumen Maintenance: Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral cast-aluminum, finned heat sink design for maximum heat rejection to provide long LED life.

Driver: Electronic Direct Current driver mounted in fixture. Comes standard with dimming. Smoothly dims down to 10% with standard Incandescent and Electronic Low Voltage dimmers.

Color Temperature: Comes with 3,000K Warm White LED's binned according to ANSI C78 377A for color temperature and chromaticity ranges. Available with other color temperatures with ANSI binning between 2700K and 6500K. To order use "-T" Suffix followed by color temperature, consult factory as extended lead times and minimum order apply.

Safety Labels: ETL/CETL listed. Suitable for damp locations. NYC approved: Calendar #41937.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.

Finish: Only available in White Reflector/White Ring*.

Color Temp: Only available in 3000K.

Base: Available in GU24 and Med Base.

COMPATIBILITY



S-GU24-MED

GU24 SOCKET
ADAPTER



LH99

STANDARD E26
HOUSING



LH99R

REMODEL E26
HOUSING

Note: Wattage limitations on compatible items must be met.

LED Details:

9W 560 Lumen Package

Color Rendering Index (CRI): 90

Color Temperature: 3,000K

Lamp Equivalents: 50W BR30

Benefit:

- Singular Diffused Optics eliminate visible LEDs
- Clean one-piece, self-flanged reflector design
- Performance exceeds 50W BR Lamp or 18W CFL
- FULL Spectrum 90 CRI Output
- Great Value
- Comes with GU24 Socket (Available with Medium Base)
- Full Color Bar Coded Retail packaging
- Energy Star Qualified

FEATURE:



ORDERING EXAMPLE : LRLD4W-BOX20

LRLD4	FINISH	COLOR TEMP	BASE
LRLD4	W-BOX20: White Reflector/White Ring*	Blank : 3000K	Blank : GU24 S-GU24-MED : Med Base

* Only sold in boxes of 20.

ID#: 2890