


Shallow Housing w/ Narrow Aperture Reflector LH1499 SERIES - 4" LOW VOLTAGE RECESSED LIGHTING



SPECIFICATION

Ceiling cut-out: 4 1/2"

Application: General purpose recessed downlight housing for low to medium height ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the desired décor and illumination.

Housing: Pre-wired housing adjusts up to a 1 1/4" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Transformer: High quality insulated transformer installed adjacent to Junction Box, bottom and top accessible. Thermally protected rated for 90° C. Available in magnetic or "noise-free" electronic.

Socket: 2-pin porcelain socket with aluminum heat sink plate. Lamp clips to trim to ensure proper and consistent positioning.

Junction Box: 16 gauge pre-wired galvanized steel Junction Box, 25 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (3) 3/4", (1) 1" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non IC rated housing must be kept 3" from insulation. IC rated housing rated for direct contact with low to medium density loosefill blown and rolled insulation. For use with high density loose fill blown insulation, reduce rated lamp wattage accordingly (roughly %15-%20).

Safety Labels: ETL/CETL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: cETL Listed

FEATURE:



Application: Used in both general and accent lighting applications. Utilizing the crisp, light output and the precision aiming capabilities of the MR16 lamps, this trim brings out the most vibrant colors from artwork and accentuates the beauty of jewelry, crystals as well as architectural features. Provides an even illumination with excellent lumen cutoff to create a dramatic lighting scene. The highly reflective surface allows for maximum lumen output.

Gasket: Supplied with gasket to prevent light leakage and unsightly heat streaks on ceiling surface.


Lens Inclusion: Clear glass protective safety lens included in packaging.

Mounting: Steel pressure springs mounted on trim to ensure positive retention inside housing.

Adjustability Lamp can be tilted 25° degrees vertically.

Accessories: Takes up to (2) 2" Media.

Label: UL Listed, cETL Listed



SHALLOW HOUSING LSH1499 12V Out 37W Max MR16

RATING	WATTAGE	VOLTAGE
LSH1499 :Non-IC Magnetic	Blank :37W	Blank :120V
LSH1499E :Non-IC Electronic	-27	:277V (Electronic*)

* Available with 120V/277V Magnetic Option, consult factory

NARROW APERTURE REFLECTOR LR1444 12V 75W Max MR16

REFLECTOR FINISH	RING FINISH
LR1444W :White	Blank :White
LR1444B :Black	B :Black
LR1444G :Gold	N :Natural
LR1444CO :All Copper*	CO :Copper
LR1444S :Satin Haze	

* Comes standard with a matching ring finish. Use "W" for White Ring.

Ordering example: LSH1499/LR1444W