
TYPE CATALOG#

LTD28320 : CYLINDER LED TRACK HEAD (2CCT/2NT) 1600LM (12W)





Application: Architecturally styled Cylinder LED track head features a durable steel body and futuristic alloy heat sink. It's small, unobtrusive size make it ideal for retail, commercial and residential applications requiring stylish design and true PAR20/PAR30 performance.

Connector: Factory Installed specification grade 2-circuit 2-Neutral track connector.

Aiming Mechanism: Unobtrusive internal aiming mechanism allows maximum adjustability while rigidly maintaining desired positioning using no visible knobs, wires or screws.

Driver: Electronic Constant Current driver integrally mounted in fixture casing.

Dimming: Works with most electronic low voltage dimming systems. Factory qualified for use with Lutron brand dimmers: SELV300P, VELV300P, NELV-450 as well as 3-way versions. Smoothly dims down to 10% of initial lumens with flicker-free operation

Lumen Maintenance: Minimum 35,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Thermal Management: Effective thermal dissipation facilitated by integral aluminum heat sink for maximum heat rejection to provide long LED life.

Color Temperature: LED Diodes comes standard in Neutral white 3,000K +/- 100K Also available in 4,000K as special order. Consult factory, extended lead times and minumum order quantities may apply

Safety Labels: ETL/CETL listed. Suitable for dry locations only.

Warranty: Covered by a 3 Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C, installations exceeding this temperature will result in reduced LED lamp life and voided warranty.

Finish: Available in All Black and All White.

Beam Spread: Available in Spot, Narrow Flood and Flood.

Color Temperature: Available in 2700K (90CRI), 3000K (90CRI) and 4000K (80CRI).

Accessories: Snoot (SNT) ship with Accessories Cap which replaces threaded Lens Cap.



COMPATIBILITY



Note: Wattage limitations on compatible items must be met.

LED Details:

20W 1600 Lumens Delivered

Color Rendering Index (CRI): 90 Color Temperature: 3000K Lamp Equivalents: 100W PAR20/PAR30

Benefits:

- High Quality 90 CRI
- Sleek Unobtrusive Design
- Dims Down to 0%!
- Concealed heat sink, LED driver, hardware, and wiring
- Precision design ensures firm positioning
- Highly adjustable, 355° Rotation/0°-90° Gimbal
- "Zero Percent Dimmin Standard" Smoothly Dims to completely off with Standard Incandescent Dimmers Hardware is included for track and canopy mount!

FEATURE:











ORDERING EXAMPLE: LTD28320B-B15-T27

LTD28320 LTD28320

FINISH

BEAM SPREAD

-B40 :Flood

COLOR TEMPERATURE

-SNT:Snoot

ACCESSORIES

:All Black :All White

-B15 :Spot -B25 : Narrow Flood

-T27 :2700K (90CRI) -T30 :3000K (90CRI)

-T40 :4000K (80CRI)

