


SP206N - CYLINDA METALLIC PENDANT (LED 9W)

SEVILLE METALLIC LED PENDANTS



SPECIFICATION

120V AC 9W CREE LED

Application: Decorative cylindrical brushed aluminum LED pendant is perfect for introducing beauty, style and intimate illumination to restaurant, hospitality, retail, commercial and high-end residential environments. Warm, lively lumen distribution when turned on, attractive aesthetics when turned off.

Cord: Clear 6' metallic cord is supplied with pendant, field-cuttable for custom installations.

Canopy: 4-3/4" x 1-1/8" Canopy mounts to standard junction box. Canopy and hardware feature Satin Nickel finish.

Thermal Management: Effective thermal dissipation facilitated by integral aluminum heatsink. Satin Nickel finish.

Dimming: Dims down to 10% using most Electronic Low Voltage (ELV) Dimmers.

Driver: Electronic Constant Current driver integrally mounted in fixture casing.

Lumen Maintenance: Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Color Temperature: Comes standard with 3,000K Warm White LED's binned according to ANSI C78 377A for color temperature and chromaticity ranges.

Finish: Available in Raw Natural Aluminum Shade, Black Shade and White Shade.

Driver: Available in 120V ELV Dimming and 120V/277V 2-Wire, ELV, and 0-10V Dimming.

Label: cUL Listed

LED Details:

9W 500 Lumens Delivered

Color Rendering Index (CRI): 80

Color Temperature: 3,000K

Lamp Equivalents: 50W PAR20 FL, 50W MR16 FL

Benefit:

- Features long life CREE XLamp LED
- Dimmable using most ELV dimmers
- Usually ships in 1-3 days
- Available in Black and White Shades
- 120V/277V 2-Wire, ELV, & 0-10V Dimming

FEATURE:



ORDERING EXAMPLE : SP206N

SP206N	FINISH	DRIVER
SP206N	Blank :Raw Natural Aluminum Shade	Blank :120V ELV Dimming
	B :Black Shade	
	W :White Shade	

ID#: 3179