


# WD1Q340: 4" SQUARE 1-DIRECTION

WALL MOUNT (IP65) 1000LM/1500LM (10W/15W)



- Uniform, low glare illumination
- Singular COB light source
- New integral emergency option
- UniDim™ dimming option with 2-wire incandescent, 3-wire, ELV or 0-10V controls
- 13' mtg. ht., 22' o.c. spacing (1000 lumen package)
- 25' mtg. ht., 22' o.c. spacing (1500 lumen package)
- 5-year limited warranty
- Photocell available
- Available with Type IV/Forward Throw Optics

## ORDERING : WD1Q340W-B10UE-DUN-EMAC-T27-LVR

### WD1Q340

| Fixture                   | Finish                           | Lumen | Optics                   | Dimming                      | Emergency Options             | LED                   | Options                     |
|---------------------------|----------------------------------|-------|--------------------------|------------------------------|-------------------------------|-----------------------|-----------------------------|
| <b>Finish</b>             |                                  |       | <b>Optics</b>            | <b>Dimming<sup>3</sup></b>   |                               | <b>LED</b>            |                             |
| White                     | (RAL 9003) <b>W</b>              |       | <i>Standard Beams</i>    | Non-Dimming (120V)           | <b>Blank</b>                  | 4000K (90 CRI)        | <b>Blank</b>                |
| Silver                    | (RAL 7037) <b>S</b>              |       | Wide Flood               | ELV and Triac (120V)         | <b>-DIN</b>                   | 2700K (90 CRI)        | <b>-T27</b>                 |
| Bronze                    | (RAL 8019) <b>BZ</b>             |       | Narrow Spot              | 0-10V (120V/277V)            | <b>UE-D10</b>                 | 2700K (97 CRI)        | <b>-T27-C97<sup>2</sup></b> |
| Black                     | (RAL 9005) <b>B</b>              |       | Spot                     | UniDim™ (120V/277V)          | <b>UE-DUN</b>                 | 3000K (90 CRI)        | <b>-T30</b>                 |
| Light Silver              | (RAL 7036) <b>LS<sup>1</sup></b> |       | Flood                    | 0-10V 1% Dimming (120V/277V) | <b>UE-D10P1</b>               | 3000K (97 CRI)        | <b>-T30-C97<sup>2</sup></b> |
| Dark Grey                 | (RAL 7015) <b>DG<sup>1</sup></b> |       | <i>CleanBeam™ Option</i> |                              |                               | 3500K (90 CRI)        | <b>-T35</b>                 |
| Metallic Gold (RAL 1001)  | <b>MG<sup>1</sup></b>            |       | 10° Pencil Beam          | <b>Emergency Options</b>     |                               | 5000K (80 CRI)        | <b>-T50</b>                 |
| Metallic Black (RAL 7021) | <b>MB<sup>1</sup></b>            |       | 15° Clean Beam           | None                         | <b>Blank</b>                  | Amber (590nm)         | <b>-TAM<sup>8</sup></b>     |
| <b>Lumen</b>              |                                  |       | 35° Clean Beam           | Remote                       | <b>-EMAC</b>                  | RGB+W Control (24VDC) | <b>-RGBWV24<sup>7</sup></b> |
| 1000lm (10W)              | <b>Blank</b>                     |       | <i>Specialty Beams</i>   | BackPack (Side Mount)        | <b>-EMB-SD<sup>6</sup></b>    | <b>Options</b>        |                             |
| 1500lm (15W)              | <b>-L13</b>                      |       | Wall Wash                | BackPack (Face Mount)        | <b>-EMB-FC<sup>6</sup></b>    | None                  | <b>Blank</b>                |
|                           |                                  |       | Forward Throw (Type IV)  | BackPack (Empty)             | <b>-EMB-BLANK<sup>5</sup></b> | Black Hexcell Louver  | <b>-LVR</b>                 |
|                           |                                  |       | Type II (30° x 60°)      |                              |                               | Cold Weather Start    | <b>-CW<sup>4,6</sup></b>    |
|                           |                                  |       |                          |                              |                               | Surge Protector       | <b>-SRG</b>                 |
|                           |                                  |       |                          |                              |                               | Photocell Sensor      | <b>-SDL</b>                 |
|                           |                                  |       |                          |                              |                               | Glare Shield          | <b>-SH</b>                  |

<sup>1</sup>Special Order Finish. Minimum order quantity (MOQ) applies. Orders less than MOQ are subject to a special paint set-up fee for the quantity ordered. Extended lead times may apply. Consult Factory.

<sup>2</sup>Special Order. Minimum order quantity (MOQ), extended lead time may apply. Consult Factory.

<sup>3</sup>Standard driver minimum starting temperature is -10°C / 14°F.

<sup>4</sup>Cold Weather Start (-CW) Starting Temperature -30°C / -22°F.

<sup>5</sup>Blank EM enclosure available for non-EM units to provide a seamless design aesthetic when EM enabled products are installed.

<sup>6</sup>(-EMB) is not compatible with (-CW) option.

<sup>7</sup>Remote Power Supplies and Control Gear required. Available with Wireless Bluetooth Casambi or DMX 512 control. Consult Factory for Details.

<sup>8</sup>(-TAM) 590nm AMBER is only available with (Blank) Wide Flood Optic.

347 Input with 0-10V available. Consult Factory for details and lead time.

Energy Efficient Chip-On-Board (COB) Singular LED Light source provides for smooth uniform light output, eliminating the multiple shadow effect seen by multiple LED source products.

Binned with 3-Step MacAdam Ellipses as recommended by Ansi Standard. Available in 2700k, 3000k, 3500k, 4000k, 5000k, RGBW, and 590nm Amber.

Custom RAL Color: Please note that we appreciate custom finishes. Custom finishes are subject to a special paint setup fee for the quantity ordered. Extended lead times may apply. Consult Factory.

## SPECIFICATION

### Application

This WD1 series single direction wall mount luminaire can be used for both interior and outdoor locations. The single reflector design can be used for direct illumination downward or indirect illumination upward for new construction or retrofit installations. Typical locations are in residential, commercial, and architectural facades and retail spaces that contain walls and/or columns.


### Housing/Arm

Housing and Arm are constructed of one piece rectilinear high grade aluminum extrusions (Alloy 6061<.04% Cu). Faceplate (with flush mounted tempered glass lens) and end caps are of a robust die cast aluminum alloy and are secured to the housing with (4) socket head tamper resistant stainless steel screws and seal the housing (top and bottom) using silicone gaskets. An aluminum alloy mounting plate with a U-bracket installs onto an electrical junction box and secures into the arm with two (2) flat head countersunk phillips head stainless steel screws.

### Mounting:

The 4-1/4" square mounting plate with U-bracket installs onto a 3-1/2" or 4" octagonal electrical junction box. For other junction box sizes see installation instructions.

### Finish:



A 7-stage electrostatic, polymer process provides an outdoor textured powder coat finish that delivers outstanding durability, superior anti-aging, resistance to corrosion and UV-degradation. Consult factory for Custom Color. (More Information)

#### Standard Finishes:

White: RAL 9003 (W)  
Silver: RAL 7037 (S)  
Bronze: RAL 8019 (BZ)  
Black: RAL 9005 (B)

#### Special Order Finishes:

Light Silver: RAL 7036 (LS)  
Dark Gray: RAL 7015 (DG)  
Metallic Gold: RAL 1001 (MG)  
Metallic Black: RAL 7021 (MB)

### Certifications and Listings:



ETL / cETL Listed to UL1598 and UL8750 standards.

Suitable wet locations. (IP65)

Assembled in USA.

IK08 rated for impact resistance.

## SPECIFICATION (Continued)

**Caution:** LITON recommends use of surge protectors on the power entering LED Housings.  
Surge damage is not covered by warranty.

### Warranty

Covered by a 5-Year Warranty to be free of defects in materials and craftsmanship.  
Fixture should not be installed in applications with ambient temperature above 50°C/122°F.  
Doing so will result in reduced lamp life and voided warranty.

### Optics

Multifaceted aluminum reflector produces low glare illumination with e light control options.

### Standard Beam:

Used for maximum light output and visible field angle.

### CleanBeam™:

Used for a direct uniform light output with minimized field angle and to enhance building aesthetics.


### LED

COB (Chip on Board) singular LED light source provides for smooth, uniform light output, eliminating the multiple imaging produced by multiple LED source optics.

**Lumen Maintenance:** Lumen Maintenance is a minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

**Lumen Options (Nominal):** 1000lm (10W)  
1500lm (15W) (-L13)

**Color Temperature:** Binned with 4-step MacAdam ellipses as per ANSI Standard recommendation.



| COLOR TEMP: | 2700K  | 3000K  | 3500K | 4000K | 5000K |
|-------------|--------|--------|-------|-------|-------|
| CRI:        | 90, 97 | 90, 97 | 90    | 90    | 80    |

Amber: 590nm

## SPECIFICATION (Continued)

### RGB+W:




**CASAMBI**

15W RGBW LED Module Illuminates surfaces up to 10 feet away. Used for applications desiring a dynamic color changing effect. RGB+W design allows fine-tuned pastel colors and saturated hues without sacrificing illumination brightness. Can be set for static colors or dynamic shows. Multiple control options available with either CASAMBI Wireless Bluetooth control or DMX 512 remote mounted decoders.

On-site commissioning and programming available.


Consult Factory for Layout Assistance and Lead Times.

| COLOR | CCT/WAVELENGTH | POWER |
|-------|----------------|-------|
| Red   | 640nm          | 3.1W  |
| Green | 520nm          | 3.1W  |
| Blue  | 450nm          | 3.1W  |
| White | 2700K          | 3.1W  |




WIRED

| Remote Power Supply | Controls                                   | Wattage         |
|---------------------|--------------------------------------------|-----------------|
| LD5-RGBW-RMTJBX     | Remote Mounted Decoder <b>-DMX512</b>      | 15W <b>-W15</b> |
|                     | Wireless Bluetooth Control <b>-CASAMBI</b> | 30W <b>-W30</b> |
|                     |                                            | 60W <b>-W60</b> |
|                     |                                            | 96W <b>-W96</b> |



Junction Box Dimensions: 11" x 2-7/8" x 1-3/4" (LxWxH)



NOTE: Power supply must be placed in dry locations only. 100 feet max for 5 wire low voltage cable 18AWG.

## SPECIFICATION (Continued)


### REMOTE LOCATION EMERGENCY INVERTER (-EMAC): 25W and 40W

For installation away from the surface of the building in remote hidden location.

- Hidden Emergency Equipment
- Must be installed in Dry Locations
- Wattage package will determine if 25W or 40W battery gets sent; corresponding wiring diagrams below
- 170 VDC output to AC DRIVER during EM mode


**Not rated for outdoor mounting. Damp location rated.**

#### <25W LOAD



|                      |                               |
|----------------------|-------------------------------|
| Input Voltage:       | 120-277VAC/60Hz               |
| Output Voltage:      | 170VDC<br>(120VAC Equivalent) |
| Wattage:             | 25W                           |
| Switching Time:      | <1s                           |
| Charging Time:       | 24h                           |
| Operating Time:      | 90 minutes                    |
| Minimum Temperature: | 0°C                           |
| Maximum Temperature: | 50°C                          |
| Maximum Lumens:      | 2200lm                        |
| Self-Diagnostic:     | No                            |


#### <40W LOAD



|                      |                               |
|----------------------|-------------------------------|
| Input Voltage:       | 120-277VAC/60Hz               |
| Output Voltage:      | 170VDC<br>(120VAC Equivalent) |
| Wattage:             | 40W                           |
| Switching Time:      | <1s                           |
| Charging Time:       | 24h                           |
| Operating Time:      | 90 minutes                    |
| Minimum Temperature: | 0°C                           |
| Maximum Temperature: | 50°C                          |
| Maximum Lumens:      | 3500lm                        |
| Self-Diagnostic:     | Yes                           |

#### >40W LOAD

- 0-10V dimmable driver required




## SPECIFICATION (Continued)

### BackPack Side Mount (-EMB-FC):


Eliminates need for long runs back to remote emergency battery location. Installs directly on building surface. Ideal for locations wanting same mounting aesthetics for Emergency and Non-Emergency fixtures without the use of remote Emergency power. Can be fed from recessed wall mounted junction box from the back of fixture or surface conduit from side of fixture.

- Wet location rated.
- 120V-347V operation.
- Self diagnostic.
- Integral surge protector for emergency driver only.
- Includes (2) 1/2" NPT knock-outs.
- Optional -EMB-BLANK can be used to maintain a common aesthetic when -EMB-FC are used.




|                          |                                                                                                                   |
|--------------------------|-------------------------------------------------------------------------------------------------------------------|
| Output Power:            | 18 Watts (Max)                                                                                                    |
| Input Power:             | 7 Watts (Max)                                                                                                     |
| Emergency Operation:     | ≥90 minutes                                                                                                       |
| Operating temp:          | 0°C/32°F to 50°C/122°F                                                                                            |
| Input Voltage:           | 120V-347 VAC                                                                                                      |
| Battery:                 | Recyclable lithium battery<br>24 Hour Recharge<br>7-10 Year Life Expectancy                                       |
| Charge Time:             | 24 hours                                                                                                          |
| Max Distance:            | 25'                                                                                                               |
| Weight:                  | 3-3/4 lbs.                                                                                                        |
| Warranty:                | 5-year                                                                                                            |
| Surge Protection:        | Integral 3,000V                                                                                                   |
| Self-diagnostic testing: | Monthly 30 sec. test, Yearly 90 min. test to verify proper emergency operation per life safety code requirements. |

### (<18W)



### (18W-200W)



## SPECIFICATION (Continued)

### Additional Options

Hexcell Louver (-LVR):

3 mm /.125" (size of the cells) - matte black finish, 45° glare cutoff, unframed.



Photocell (/SDL):

Allows for energy savings when illumination is not need during between dawn to dusks. Cuts off power to LED's during day time or in illuminated environments.



Voltage: 120V, 277V

Power Consumption .5W

On/Off Levels: On @ 0-2fc / Off @ 2fc or more

Warranty: 2-Year / 5,000 Cycles

Sensor Size: 3/8"

Rating: UL/cUL


Surge Suppressor (/SRG):

Protects driver against surges in line voltage/current (20KV, 1.2/50μS & 10KA, 8/20μS).

Provides a positive indication of end-of-life by opening voltage to the load.

Surge suppressor is a perishable device requiring periodic replacement.

Not a warrantied item.



## SPECIFICATION (Continued)

### Electrical

LED Driver: AC 50/60Hz Electronic Direct Current Class 2 driver integrally mounted.  
Power Factor > 0.90. See Dimming Section for voltage and wiring.

-10 ° C/14 ° F Starting Temp

-30 ° C/-22 ° F Starting Temp

\* For cold weather application add -CW option.

### Dimming Options

#### ELV and TRIAC Driver 120V (-DIN):

Compatible with electronic low voltage, and 2-Wire incandescent dimmers. Also known as leading edge, Reverse Phase, Forward Phase dimming. Allows smooth dimming down to 5% depending upon the dimmer's limitations.


#### 0-10V Driver 120V/277V (UE-D10):

Compatible with most existing 0-10V systems. Also known as fluorescent or 5-Wire dimming. Allows smooth dimming down to 5% depending upon the dimmer's limitations. Compatible with daylight harvesting controls.


#### UniDim™ Driver 120V/277V (UE-DUN):

All in one ELV and TRIAC phase dimming (120V only), and 0-10V dimming (120V/277V). Works with most 3-Wire ELV, 2-Wire incandescent and 120V/277V 5-Wire 0-10V fluorescent dimmers.


Incandescent/Phase Wiring  
ELV




TRIAC




0 - 10V Wiring




Incandescent/Phase Wiring  
ELV



TRIAC



0 - 10V Wiring




## WD1Q340 (L15) PHOTOMETRY


### Footcandles On Wall

■ .5 fc ■ 1.0 fc ■ 2.0 fc ■ 5.0 fc


**STANDARD BEAM – Wide Flood (Blank)**  
3 ft Grid




**CLEANBEAM™ – (-B02)**  
3 ft Grid




**CLEANBEAM™ – (-CB20)**  
3 ft Grid



**CLEANBEAM™ – (-CB35)**  
3 ft Grid




**SPECIALTY BEAM – Wall Wash (-BWW)**  
3 ft Grid




### FOOTCANDLES ON WALL AND GROUND

■ .5 fc ■ 1.0 fc ■ 2.0 fc ■ 5.0 fc


**STANDARD BEAM – Wide Flood (Blank)**  
3 ft Grid



**SPECIALTY BEAM – Type II (-BII)**  
3 ft Grid



**SPECIALTY BEAM – Type IV (-BIV)**  
3 ft Grid




## PHOTOMETRY – WD1Q340 (L15) (Cont.)


### Footcandles On Ground (2 - Fixture Overlap)

■ .5 fc ■ 1.0 fc ■ 2.0 fc ■ 5.0 fc


**STANDARD BEAM – WIDE FLOOD 8 ft Mtg Ht**




**STANDARD BEAM – WIDE FLOOD 16 ft Mtg Ht**




**SPECIALTY BEAM – TYPE IV (-BIV) 8 ft Mtg Ht**




**SPECIALTY BEAM – TYPE IV (-BIV) 16 ft Mtg Ht**



**SPECIALTY BEAM – TYPE II (-BII) 8 ft Mtg Ht**



**SPECIALTY BEAM – TYPE II (-BII) 16 ft Mtg Ht**



## LUMEN OUTPUT / LPW /BUG RATING

| LM             | W    | Beam Spread | -T27 (2700K, 90 CRI) |     |       |   |   |   | -T30 (3000K, 90 CRI) |     |       |   |   |   | -T35 (3500K, 90 CRI) |     |       |   |   |   | Blank (4000K, 90 CRI) |     |       |   |   |   | -T50 (5000K, 80 CRI) |     |       |   |   |   |
|----------------|------|-------------|----------------------|-----|-------|---|---|---|----------------------|-----|-------|---|---|---|----------------------|-----|-------|---|---|---|-----------------------|-----|-------|---|---|---|----------------------|-----|-------|---|---|---|
|                |      |             | LM                   | LPW | cd    | B | U | G | LM                   | L/W | cd    | B | U | G | LM                   | LPW | cd    | B | U | G | LM                    | LPW | cd    | B | U | G | LM                   | LPW | cd    | B | U | G |
| 1000 lm        | 13.9 | Wide FL     | 594                  | 43  | 788   | 1 | 0 | 0 | 841                  | 60  | 821   | 1 | 0 | 0 | 852                  | 61  | 832   | 1 | 0 | 0 | 854                   | 61  | 834   | 1 | 0 | 0 | 1018                 | 73  | 994   | 1 | 0 | 0 |
|                |      | -B02        | 175                  | 13  | 569   | 0 | 0 | 0 | 250                  | 18  | 593   | 0 | 0 | 0 | 254                  | 18  | 601   | 0 | 0 | 0 | 254                   | 18  | 602   | 0 | 0 | 0 | 303                  | 22  | 717   | 0 | 0 | 0 |
|                |      | -CB20       | 284                  | 20  | 660   | 1 | 0 | 0 | 406                  | 29  | 687   | 1 | 0 | 0 | 411                  | 30  | 697   | 1 | 0 | 0 | 412                   | 30  | 698   | 1 | 0 | 0 | 491                  | 35  | 832   | 1 | 0 | 0 |
|                |      | -CB35       | 360                  | 26  | 598   | 1 | 0 | 0 | 513                  | 37  | 622   | 1 | 0 | 0 | 520                  | 37  | 631   | 1 | 0 | 0 | 521                   | 37  | 632   | 1 | 0 | 0 | 621                  | 45  | 753   | 1 | 0 | 0 |
|                |      | -B10        | 750                  | 54  | 11642 | 1 | 0 | 0 | 1070                 | 77  | 12120 | 1 | 0 | 0 | 1085                 | 78  | 12290 | 1 | 0 | 0 | 1087                  | 78  | 12313 | 1 | 0 | 0 | 1295                 | 93  | 14674 | 1 | 0 | 0 |
|                |      | -B20        | 682                  | 49  | 4355  | 1 | 0 | 0 | 1043                 | 75  | 4534  | 1 | 0 | 0 | 1058                 | 76  | 4597  | 1 | 0 | 0 | 1060                  | 76  | 4606  | 1 | 0 | 0 | 1263                 | 91  | 5489  | 1 | 0 | 0 |
|                |      | -B45        | 755                  | 54  | 1913  | 1 | 0 | 0 | 1026                 | 74  | 1991  | 1 | 0 | 0 | 1040                 | 75  | 2019  | 1 | 0 | 0 | 1042                  | 75  | 2023  | 1 | 0 | 0 | 1242                 | 89  | 2411  | 1 | 0 | 0 |
|                |      | -BII        | 694                  | 50  | 754   | 2 | 0 | 0 | 989                  | 71  | 784   | 2 | 0 | 0 | 1003                 | 72  | 795   | 2 | 0 | 0 | 1005                  | 72  | 797   | 2 | 0 | 0 | 1198                 | 86  | 950   | 2 | 0 | 0 |
|                |      | -BWW        | 596                  | 43  | 703   | 1 | 0 | 0 | 850                  | 61  | 732   | 1 | 0 | 0 | 862                  | 62  | 743   | 1 | 0 | 0 | 864                   | 62  | 744   | 1 | 0 | 0 | 1030                 | 74  | 887   | 1 | 0 | 0 |
| -L15 (1500 lm) | 20.6 | -BIV        | 596                  | 43  | 703   | 1 | 0 | 0 | 850                  | 61  | 732   | 1 | 0 | 0 | 862                  | 62  | 743   | 1 | 0 | 0 | 864                   | 62  | 744   | 1 | 0 | 0 | 1030                 | 74  | 887   | 1 | 0 | 0 |
|                |      | Wide FL     | 1440                 | 70  | 1057  | 1 | 0 | 0 | 1499                 | 73  | 1100  | 1 | 0 | 0 | 1520                 | 74  | 1116  | 1 | 0 | 0 | 1523                  | 74  | 1118  | 1 | 0 | 0 | 1815                 | 88  | 1332  | 1 | 0 | 0 |
|                |      | -B02        | 429                  | 21  | 780   | 1 | 1 | 0 | 447                  | 22  | 812   | 1 | 1 | 0 | 453                  | 22  | 823   | 1 | 1 | 0 | 454                   | 22  | 825   | 1 | 1 | 0 | 541                  | 26  | 983   | 1 | 1 | 0 |
|                |      | -CB20       | 691                  | 34  | 902   | 1 | 0 | 0 | 719                  | 35  | 939   | 1 | 0 | 0 | 729                  | 35  | 952   | 1 | 0 | 0 | 731                   | 35  | 954   | 1 | 0 | 0 | 871                  | 42  | 1137  | 1 | 0 | 0 |
|                |      | -CB35       | 874                  | 42  | 814   | 1 | 0 | 0 | 910                  | 44  | 847   | 1 | 0 | 0 | 923                  | 45  | 859   | 1 | 0 | 0 | 924                   | 45  | 861   | 1 | 0 | 0 | 1102                 | 53  | 1026  | 1 | 0 | 0 |
|                |      | -B10        | 1808                 | 88  | 15548 | 1 | 0 | 0 | 1882                 | 91  | 16187 | 1 | 0 | 0 | 1909                 | 93  | 16414 | 1 | 0 | 0 | 1912                  | 93  | 16445 | 1 | 0 | 0 | 2279                 | 111 | 19598 | 1 | 0 | 0 |
|                |      | -B20        | 1757                 | 85  | 5768  | 2 | 0 | 0 | 1830                 | 89  | 6005  | 2 | 0 | 0 | 1855                 | 90  | 6089  | 2 | 0 | 0 | 1859                  | 90  | 6101  | 2 | 0 | 0 | 2215                 | 108 | 7271  | 2 | 0 | 0 |
|                |      | -B45        | 1313                 | 64  | 2549  | 2 | 0 | 0 | 1367                 | 66  | 2654  | 2 | 0 | 0 | 1386                 | 67  | 2691  | 2 | 0 | 0 | 1389                  | 67  | 2696  | 2 | 0 | 0 | 1655                 | 80  | 3213  | 2 | 0 | 0 |
|                |      | -BII        | 1686                 | 82  | 1029  | 2 | 0 | 0 | 1756                 | 85  | 1071  | 2 | 0 | 0 | 1780                 | 86  | 1086  | 2 | 0 | 0 | 1784                  | 87  | 1088  | 2 | 0 | 0 | 2126                 | 103 | 1297  | 2 | 0 | 0 |
|                |      | -BWW        | 1131                 | 55  | 748   | 1 | 0 | 0 | 1177                 | 57  | 779   | 1 | 0 | 0 | 1194                 | 58  | 789   | 1 | 0 | 0 | 1196                  | 58  | 791   | 1 | 0 | 0 | 1423                 | 69  | 941   | 1 | 0 | 0 |
|                |      | -BIV        | 1131                 | 55  | 748   | 1 | 0 | 0 | 1177                 | 57  | 779   | 1 | 0 | 0 | 1194                 | 58  | 789   | 1 | 0 | 0 | 1196                  | 58  | 791   | 1 | 0 | 0 | 1425                 | 69  | 943   | 1 | 0 | 0 |