


DL34R - PHOTOMETRY 4" RECESSED DOWNLIGHT

DL34RW-L12UE-DUN-T40 (1200lm / 15W, 4000K, CRI: 80)

System Power	:14.4W	Multipliers	
Test Date	:1/10/2020	CCT	
Beam Angle 50%	:67.0°	5000K	1.01
Field Angle 10%	:88.1°	4000K	1.00
Color Temperature	:4000K	3500K	0.99
CRI	:80	3000K	0.98
Lumens Delivered	:1184lm	2700K	0.94
CBCP	:1139cd	CRI	
Power Factor	:0.99	80	1.00
		90	0.86

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	7.9'	31.6
8.0'	10.6'	17.8
10.0'	13.2'	11.4
12.0'	15.9'	7.9
14.0'	18.5'	5.8

DL34RWUE-DUN-T40 (1500lm / 21W, 4000K, CRI: 80)

System Power	:20.7W	Multipliers	
Test Date	:1/10/2020	CCT	
Beam Angle 50%	:67.0°	5000K	1.01
Field Angle 10%	:88.3°	4000K	1.00
Color Temperature	:4000K	3500K	0.99
CRI	:80	3000K	0.98
R9 Value	:0	2700K	0.94
Lumens Delivered	:1561.7lm	CRI	
CBCP	:1500cd	80	1.00
Power Factor	:0.99	90	0.86

CANDELA TABULATION



FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
8.0'	10.6'	23.4
10.0'	13.2'	15.0
12.0'	15.9'	10.4
14.0'	18.5'	7.7
16.0'	21.2'	5.9