


PHOTOMETRY

LCALDJ5W-L25 (2500lm, 15°, 3000K)


D = Distance from ceiling to ground/wall
H = Distance to FC center of beam
FC = Footcandles
W = Beam width
L = Beam length



LCALDJ5W-L25-B15UE-DUN-40 (Surface Mount Wall)

System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	13.9°
Field Angle 10% :	27.4°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2341.3
BCBP :	18717
Power Factor :	> 0.9

MULTIPLIERS	
LUMENS	
3500lm (-L35) :	1.41
2500lm (-L25) :	1.00
CRI	CCT
90 CRI : 1.00	4000K : 1.02
97 CRI : 0.89	3500K : 1.01
	3000K : 1.00
	2700K : 0.96






LCALDJ5W-L25-B15UE-DUN-40/-STM12/-STM12J/-1C1N

LCALDJ5W-L25-B15UE-DUN-40 (Surface Mount Ceiling)

System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	13.9°
Field Angle 10% :	27.4°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2341.3
BCBP :	18717
Power Factor :	> 0.9

MULTIPLIERS	
LUMENS	
3500lm (-L35) :	1.41
2500lm (-L25) :	1.00
CRI	CCT
90 CRI : 1.00	4000K : 1.03
97 CRI : 0.89	3500K : 1.02
	3000K : 1.00
	2700K : 0.96

Mounting		Horizontal Angle														
		A° = 5°					A° = 15°					A° = 30°				
Surface Mount (Wall) (-40)	H	D	FC	W	L	H	D	FC	W	L	H	D	FC	W	L	H
		10.0'	0.8'	196.3	2.4'	2.4'	10.0'	2.6'	178.8	2.5'	2.5'	10.0'	5.6'	128.4	2.7'	3.2'
		12.0'	1.0'	135.0	2.9'	2.9'	12.0'	3.1'	122.9	3.0'	3.1'	12.0'	6.8'	88.4	3.3'	3.8'
		14.0'	1.2'	98.5	3.4'	3.4'	14.0'	3.7'	89.7	3.5'	3.6'	14.0'	7.9'	64.5	3.9'	4.5'
		16.0'	1.4'	75.0	3.8'	3.9'	16.0'	4.2'	68.3	4.0'	4.1'	16.0'	9.1'	49.1	4.4'	5.1'



		Horizontal Angle								Vertical Angle (Fixture calculated at aiming point (90°) to horizontal surface)															
		No Tilt				A° = 30°				A° = 30°				A° = 45°				A° = 60°							
Mounting		H	FC	W	L	H	D	FC	W	L	D	H	FC	W	L	D	H	FC	W	L					
Surface Mount (Ceiling) (-40)	10.0'	220.0	2.2'	2.2'		10.0'	5.3'	141.8	2.6'	3.0'	8.0	14.6'	36.6	3.9'	8.2'	8.0'	8.7'	103.4	2.8'	4.0'	8.0'	5.3'	190.0	2.3'	2.6'
	12.0'	148.6	2.7'	2.7'		12.0'	6.5	95.9	3.2'	3.7'	9.0'	16.3'	28.9	4.4'	9.2'	9.0'	9.7'	81.7	3.1'	4.5'	9.0'	5.9'	150.1	2.5'	2.9'
	14.0'	107.0	3.2'	3.2'		14.0'	7.7'	69.1	3.7'	4.3'	10.0'	18.1'	23.4	4.9'	10.2'	10.0'	10.7'	66.2	3.4'	4.9'	10.0'	6.4'	121.6	2.8'	3.3'
	16.0'	80.8	3.7'	3.7'		16.0'	8.8'	52.2	4.3'	5.0'	11.0'	19.8'	19.3	5.4'	11.2'	11.0'	11.7'	54.7	3.8'	5.4'	11.0'	7.6'	100.5	3.1'	3.6'
	18.0'	63.1	4.2'	4.2'		18.0'	10.0'	40.8	4.9'	5.6'	12.0'	21.5'	16.2	5.9'	12.2'	12.0'	12.7'	46.0	4.1'	5.9'	12.0'	7.6'	84.4	3.4'	3.9'

LCALDJ5W-L25-B15UE-DUN-STM12 (Stem Pendant)

System Power :	30.0W
Test Date :	9/5/2018
Beam Angle 50% :	13.9°
Field Angle 10% :	27.4°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2341.3
BCBP :	18717
Power Factor :	> 0.9

MULTIPLIERS	
LUMENS	
3500lm (-L35) :	1.41
2500lm (-L25) :	1.00
CRI	CCT
90 CRI : 1.00	4000K : 1.02
97 CRI : 0.89	3500K : 1.01
	3000K : 1.00
	2700K : 0.96

12" Stem Pendant (-STM12)	10.0'	273.1	2.0'	2.0'	10.0'	4.8'	175.8	2.3'	2.7'	8.0'	15.5'	36.6	3.9'	8.2'	8.0'	9.6'	103.4	2.8'	4.0'	8.0'	6.2'	190.0	2.3'	2.6'
	12.0'	177.2	2.5'	2.5'	12.0'	6.0'	114.3	2.9'	3.4'	9.0'	17.3'	28.9	4.4'	9.2'	9.0'	10.6'	81.7	3.1'	4.5'	9.0'	6.8'	150.1	2.5'	2.9'
	14.0'	124.2	3.0'	3.0'	14.0'	7.1'	80.2	3.5'	4.0'	10.0'	19.0'	23.4	4.9'	10.2'	10.0'	11.6'	66.2	3.4'	4.9'	10.0'	7.4'	121.6	2.8'	3.3'
	16.0'	91.8	3.5'	3.5'	16.0'	8.3'	59.3	4.0'	4.7'	11.0'	20.7'	19.3	5.4'	11.2'	11.0'	12.6'	54.7	3.8'	5.4'	11.0'	8.2'	100.5	3.1'	3.6'
	18.0'	70.6	4.0'	4.0'	18.0'	9.4'	45.7	4.6'	5.3'	12.0'	22.5'	16.2	5.9'	12.2'	12.0'	13.6'	46.0	4.1'	5.9'	12.0'	8.5'	84.4	3.4'	3.9'
12" Stem Pendant Adjustable (-STM12J)	10.0'	287.1	2.0'	2.0'	10.0'	4.7'	185.2	2.3'	2.6'	8.0'	15.8'	36.6	3.9'	8.2'	8.0'	9.9'	103.4	2.8'	4.0'	8.0'	6.4'	190.0	2.3'	2.6'
	12.0'	184.4	2.5'	2.5'	12.0'	5.8'	119.1	2.8'	3.3'	9.0'	17.5'	28.9	4.4'	9.2'	9.0'	10.9'	81.7	3.1'	4.5'	9.0'	7.0'	150.1	2.5'	2.9'
	14.0'	128.4	2.9'	2.9'	14.0'	7.0'	83.0	3.4'	4.0'	10.0'	19.2'	23.4	4.9'	10.2'	10.0'	11.9'	66.2	3.4'	4.9'	10.0'	7.6'	121.6	2.8'	3.3'
	16.0'	94.5	3.4'	3.4'	16.0'	8.1'	61.1	4.0'	4.6'	11.0'	21.0'	19.3	5.4'	11.2'	11.0'	12.9'	54.7	3.8'	5.4'	11.0'	8.2'	100.5	3.1'	3.6'
	18.0'	72.4	3.9'	3.9'	18.0'	9.3'	46.9	4.5'	5.3'	12.0'	22.7'	16.2	5.9'	12.2'	12.0'	13.9'	46.0	4.1'	5.9'	12.0'	8.7'	84.4	3.4'	3.9'

LCALDJ5W-L25-B15UE-DUN-1C1N (Track)

System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	13.9°
Field Angle 10% :	27.4°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2341.3
BCBP :	18717
Power Factor :	> 0.9


MULTIPLIERS	
LUMENS	
3500lm (-L35) :	1.41
2500lm (-L25) :	1.00
CRI	CCT
90 CRI : 1.00	4000K : 1.03
97 CRI : 0.89	3500K : 1.02
	3000K : 1.00
	2700K : 0.96

Track (-1C1N, -2C2N, & -3C1N)	10.0'	228.1	2.2'	2.2'	10.0'	5.3'	146.7	2.6'	3.0'	8.0'	14.8'	36.6	3.9'	8.2'	8.0'	8.9'	103.4	2.8'	4.0'	8.0'	5.4'	190.0	2.3'	1.0'
	12.0'	153.1	2.7'	2.7'	12.0'	6.4'	98.6	3.1'	3.6'	9.0'	16.5'	28.9	4.4'	9.2'	9.0'	9.9'	81.7	3.1'	4.5'	9.0'	6.0'	150.1	2.5'	1.4'
	14.0'	109.8	3.2'	3.2'	14.0'	7.6'	70.8	3.7'	4.3'	10.0'	18.2'	23.4	4.9'	10.2'	10.0'	10.9'	66.2	3.4'	4.9'	10.0'	6.6'	121.6	2.8'	1.7'
	16.0'	82.6	3.7'	3.7'	16.0'	8.7'	53.3	4.3'	4.9'	11.0'	19.9'	19.3	5.4'	11.2'	11.0'	11.9'	54.7	3.8'	5.4'	11.0'	7.1'	100.5	3.1'	2.1'
	18.0'	64.3	4.2'	4.2'	18.0'	9.9'	41.6	4.8'	5.6'	12.0'	21.7'	16.2	5.9'	12.2'	12.0'	12.9'	46.0	4.1'	5.9'	12.0'	7.7'	84.4	3.4'	2.4'

PHOTOMETRY

LCALDJ5W-L25 (2500lm, 25°, 3000K)


D = Distance from ceiling to ground/wall
H = Distance to FC center of beam
FC = Footcandles
W = Beam width
L = Beam length



LCALDJ5W-L25-B25UE-DUN-40 (Surface Mount Wall)

System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	22.3°
Field Angle 10% :	50.9°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2330.4
CBP :	9061
Power Factor :	> 0.9

MULTIPLIERS	
LUMENS	
3500lm (-L35): 1.41	
2500lm (-L25): 1.00	
CRI	CCT
90 CRI: 1.00	4000K: 1.02
97 CRI: 0.89	3500K: 1.01
	3000K: 1.00
	2700K: 0.96






LCALDJ5W-L25-B25UE-DUN-40/-STM12/-1C1N

LCALDJ5W-L25-B25UE-DUN-40 (Surface Mount Ceiling)

System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	22.3°
Field Angle 10% :	50.9°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2330.4
CBP :	9061
Power Factor :	> 0.9

MULTIPLIERS	
LUMENS	
3500lm (-L35): 1.41	
2500lm (-L25): 1.00	
CRI	CCT
90 CRI: 1.00	4000K: 1.02
97 CRI: 0.89	3500K: 1.01
	3000K: 1.00
	2700K: 0.96

Mounting		Horizontal Angle														
		A° = 5°					A° = 15°					A° = 30°				
Surface Mount (Wall) (-40)	H	D	FC	W	L	H	D	FC	W	L	H	D	FC	W	L	H
		6.0'	0.5'	274.9	2.3'	2.3'	6.0'	1.5'	250.2	2.3'	2.4'	6.0'	3.3'	179.3	2.6'	3.1'
		8.0'	0.7'	150.8	3.1'	3.1'	8.0'	2.1'	137.3	3.1'	3.3'	8.0'	4.5'	98.5	3.5'	4.1'
		10.0'	0.8'	95.0	3.8'	3.9'	10.0'	2.6'	86.6	4.0'	4.1'	10.0'	5.6'	62.2	4.4'	5.2'
		12.0'	1.0'	65.3	4.6'	4.7'	12.0'	3.1'	59.5	4.8'	5.0'	12.0'	6.8'	42.8	5.3'	6.2'
	H	D	FC	W	L	H	D	FC	W	L	H	D	FC	W	L	H
		14.0'	1.2'	47.7	5.4'	5.4'	14.0'	3.7'	43.4	5.6'	5.8'	14.0'	7.9'	31.2	6.2'	7.3'
		16.0'	1.4'	33.8	6.2'	6.2'	16.0'	4.3'	31.2	6.2'	6.2'	16.0'	9.1'	22.9	6.8'	7.3'
		18.0'	1.6'	25.0	7.0'	7.0'	18.0'	4.9'	22.9	7.0'	7.0'	18.0'	9.9'	17.3	7.4'	7.3'
		20.0'	1.8'	18.8	7.8'	7.8'	20.0'	5.5'	17.3	7.8'	7.8'	20.0'	10.7'	13.4	7.8'	7.3'



LCALDJ5W-L25-B25UE-DUN-STM12 (Stem Pendant)

System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	22.3°
Field Angle 10% :	50.9°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2330.4
CBP :	9061
Power Factor :	> 0.9

MULTIPLIERS	
LUMENS	
3500lm (-L35): 1.41	
2500lm (-L25): 1.00	
CRI	CCT
90 CRI: 1.00	4000K: 1.02
97 CRI: 0.89	3500K: 1.01
	3000K: 1.00
	2700K: 0.96

Horizontal Angle										Vertical Angle (Fixture calculated at aiming point (90°) to horizontal surface)															
Mounting	No Tilt				A° = 30°					A° = 30°					A° = 45°					A° = 60°					
	H	FC	W	L	H	D	FC	W	L	D	H	FC	W	L	D	H	FC	W	L	D	H	FC	W	L	
Surface Mount (Ceiling) (-40)	6.0'	332.1	2.1'	2.1'	6.0'	3.0'	212.7	2.4'	2.8'	5.0'	9.4'	45.3	3.9'	8.9'	5.0'	5.7'	128.1	2.8'	4.1'	5.0'	3.5'	235.4	2.3'	2.7'	
	8.0'	173.7	2.8'	2.8'	8.0'	4.2'	111.6	3.3'	3.9'	6.0'	11.1'	31.5	4.7'	10.7'	6.0'	6.7'	89.0	3.3'	4.9'	6.0'	4.1'	163.5	2.7'	3.2'	
	10.0'	106.5	3.6'	3.6'	10.0'	5.3'	68.6	4.2'	4.9'	7.0'	12.9'	23.1	5.5'	12.5'	7.0'	7.7'	65.4	3.9'	5.7'	7.0'	4.7'	120.1	3.2'	3.7'	
	12.0'	71.9	4.4'	4.4'	12.0'	6.5'	46.4	5.1'	6.0'	8.0'	14.6'	17.7	6.3'	14.3'	8.0'	8.7'	50.1	4.5'	6.6'	8.0'	5.3'	92.0	3.6'	4.3'	
	14.0'	51.8	5.2'	5.2'	14.0'	7.7'	33.5	6.0'	7.1'	9.0'	16.3'	14.0	7.1'	16.1'	9.0'	9.7'	39.5	5.0'	7.4'	9.0'	5.9'	72.7	4.1'	4.8'	
12" Stem Pendant (-STM12)	6.0'	495.1	1.7'	1.7'	6.0'	2.5'	316.1	2.0'	2.3'	5.0'	10.3'	45.3	3.9'	8.9'	5.0'	6.6'	128.1	2.8'	4.1'	5.0'	4.5'	235.4	2.3'	2.7'	
	8.0'	229.9	2.5'	2.5'	8.0'	3.6	147.6	2.9'	3.4'	6.0'	12.1'	31.5	4.7'	10.7'	6.0'	7.6'	89.0	3.3'	4.9'	6.0'	5.1'	163.5	2.7'	3.2'	
	10.0'	132.2	3.3'	3.3'	10.0'	4.8	85.1	3.8'	4.4'	7.0'	13.8'	23.1	5.5'	12.5'	7.0'	8.6'	65.4	3.9'	5.7'	7.0'	5.6'	120.1	3.2'	3.7'	
	12.0'	85.8	4.1'	4.1'	12.0'	6.0	55.3	4.7'	5.5'	8.0'	15.5'	17.7	6.3'	14.3'	8.0'	9.6'	50.1	4.5'	6.6'	8.0'	6.2'	92.0	3.6'	4.3'	
	14.0'	60.1	4.8'	4.8'	14.0'	7.1'	38.8	5.6'	6.6'	9.0'	17.3'	14.0	7.1'	16.1'	9.0'	10.6'	39.5	5.0'	7.4'	9.0'	6.8'	72.7	4.1'	4.8'	
12" Stem Pendant Adjustable (-STM12J)	6.0'	545.8	1.6'	1.6'	6.0'	2.4'	349.9	1.9'	2.2'	5.0'	10.6'	45.3	3.9'	8.9'	5.0'	6.9'	128.1	2.8'	4.1'	5.0'	4.7'	235.4	2.3'	2.7'	
	8.0'	245.6	2.4'	2.4'	8.0'	3.5	158.1	2.8'	3.2'	6.0'	12.3'	31.5	4.7'	10.7'	6.0'	7.9'	89.0	3.3'	4.9'	6.0'	5.3'	163.5	2.7'	3.2'	
	10.0'	139.0	3.2'	3.2'	10.0'	4.7	89.7	3.7'	4.3'	7.0'	14.0'	23.1	5.5'	12.5'	7.0'	8.9'	65.4	3.9'	5.7'	7.0'	5.9'	120.1	3.2'	3.7'	
	12.0'	89.3	4.0'	4.0'	12.0'	5.8	57.7	4.6'	5.4'	8.0'	15.8'	17.7	6.3'	14.3'	8.0'	9.9'	50.1	4.5'	6.6'	8.0'	6.4'	92.0	3.6'	4.3'	
	14.0'	62.1	4.8'	4.8'	14.0'	7.0	40.2	5.5'	6.4'	9.0'	17.5'	14.0	7.1'	16.1'	9.0'	10.9'	39.5	5.0'	7.4'	9.0'	7.0'	72.7	4.1'	4.8'	
	</																								

LCALDJ5W-L25-B25UE-DUN-1C1N (Track)


System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	22.3°
Field Angle 10% :	50.9°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2330.4
CBP :	9061
Power Factor :	> 0.9

MULTIPLIERS	
LUMENS	
3500lm (-L35): 1.41	
2500lm (-L25): 1.00	
CRI	CCT
90 CRI: 1.00	4000K: 1.02
97 CRI: 0.89	3500K: 1.01
	3000K: 1.00
	2700K: 0.96

PHOTOMETRY

LCALDJ5W-L25 (2500lm, 45°, 3000K)

D = Distance from ceiling to ground/wall
H = Distance to FC center of beam
FC = Footcandle
W = Beam width
L = Beam length



LCALDJ5W-L25UE-DUN-40 (Surface Mount Wall)

System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	40.9°
Field Angle 10% :	71.3°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2286
CBP :	3999
Power Factor :	> 0.9

MULTIPLIERS

LUMENS

3500lm (-L35): 1.41

2500lm (-L25): 1.00

CRI

CCT

90 CRI: 1.00


97 CRI: 0.89

4000K: 1.02

3500K: 1.01

3000K: 1.00

2700K: 0.96



LCALDJ5W-L25UE-DUN-40/-STM12/-STM12 J/-1C1N

LCALDJ5W-L25UE-DUN-40 (Surface Mount Ceiling)

System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	40.9°
Field Angle 10% :	71.3°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2286
CBP :	3999
Power Factor :	> 0.9

MULTIPLIERS

LUMENS

3500lm (-L35): 1.41

2500lm (-L25): 1.00

CRI

CCT

90 CRI: 1.00




97 CRI: 0.89

4000K: 1.02

3500K: 1.01

3000K: 1.00

2700K: 0.96



LCALDJ5W-L25UE-DUN-STM12 (Stem Pendant)

System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	40.9°
Field Angle 10% :	71.3°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2286
CBP :	3999
Power Factor :	> 0.9

MULTIPLIERS

LUMENS

3500lm (-L35): 1.41

2500lm (-L25): 1.00

CRI

CCT

90 CRI: 1.00

97 CRI: 0.89

4000K: 1.02

3500K: 1.01

3000K: 1.00

2700K: 0.96

Mounting	Horizontal Angle														
	A° = 5°					A° = 15°					A° = 30°				
	H	D	FC	W	L	H	D	FC	W	L	D	H	FC	W	L
Surface Mount (Wall) (-40)	8.0'	0.7'	66.5	5.8'	5.8'	8.0'	2.1'	60.6	6.0'	6.2'	8.0'	4.5'	43.5	6.7'	8.1'
	9.0'	0.8'	52.1	6.5'	6.6'	9.0'	2.3'	47.5	6.7'	7.0'	9.0'	5.0'	34.1	7.5'	9.1'
	10.0'	0.8'	41.9	7.3'	7.3'	10.0'	2.6'	38.2	7.5'	7.8'	10.0'	5.6'	27.4	8.4'	10.1'
	11.0'	0.9'	34.5	8.0'	8.1'	11.0'	2.9'	31.4	8.3'	8.6'	11.0'	6.2'	22.6	9.2'	11.2'
	12.0'	1.0'	28.8	8.8'	8.8'	12.0'	3.1'	26.3	9.0'	9.5'	12.0'	6.8'	18.9	10.1'	12.2'

Mounting	Horizontal Angle										Vertical Angle (Fixture calculated at aiming point (90°) to horizontal surface)									
	No Tilt					A° = 30°					A° = 30°					A° = 45°				
	H	FC	W	L		H	D	FC	W	L	D	H	FC	W	L	D	H	FC	W	L
Surface Mount (Ceiling) (-40)	8.0'	76.6	5.4'	5.4'		8.0'	4.2'	49.3	6.3'	7.6'	3.0'	5.9'	55.5	4.5'	15.4'	3.0'	3.7'	157.1	3.2'	5.2'
	9.0'	59.1	6.1'	6.1'		9.0'	4.8'	38.1	7.1'	8.6'	4.0'	7.7'	31.2	6.0'	20.5'	4.0'	4.7'	88.4	4.2'	6.9'
	10.0'	47.0	6.9'	6.9'		10.0'	5.3'	30.3	8.0'	9.7'	5.0'	9.4'	20.0	7.5'	25.6'	5.0'	5.7'	56.6	5.3'	8.7'
	11.0'	38.3	7.6'	7.6'		11.0'	5.9'	24.7	8.8'	10.7'	6.0'	11.1'	13.9	8.9'	30.7'	6.0'	6.7'	39.3	6.3'	10.4'
	12.0'	31.7	8.4'	8.4'		12.0'	6.5'	20.5	9.7'	11.7'	7.0'	12.9'	10.2	10.4'	35.8'	7.0'	7.7'	28.9	7.4'	12.1'

12" Stem Pendant (-STM12)	8.0'	101.5	4.7'	4.7'		8.0'	3.6'	65.1	5.4'	6.6'	3.0'	6.9'	55.5	4.5'	15.4'	3.0'	4.6'	157.1	3.2'	5.2'
	9.0'	75.5	5.4'	5.4'		9.0'	4.2'	48.5	6.3'	7.6'	4.0'	8.6'	31.2	6.0'	20.5'	4.0'	5.6'	88.4	4.2'	6.9'
	10.0'	58.4	6.2'	6.2'		10.0'	4.8'	37.6	7.2'	8.7'	5.0'	10.3'	20.0	7.5'	25.6'	5.0'	6.6'	56.6	5.3'	8.7'
	11.0'	46.5	6.9'	6.9'		11.0'	5.4'	29.9	8.0'	9.7'	6.0'	12.1'	13.9	8.9'	30.7'	6.0'	7.6'	39.3	6.3'	10.4'
	12.0'	37.9	7.7'	7.7'		12.0'	6.0'	24.4	8.9'	10.8'	7.0'	13.8'	10.2	10.4'	35.8'	7.0'	8.6'	28.9	7.4'	12.1'

12" Stem Pendant Adjustable (-STM12J)	8.0'	108.4	4.5'	4.5'		8.0'	3.5'	69.8	5.3'	6.4'	3.0'	7.1'	55.5	4.5'	15.4'	3.0'	4.9'	157.1	3.2'	5.2'
	9.0'	79.9	5.3'	5.3'		9.0'	4.1'	51.5	6.1'	7.4'	4.0'	8.8'	31.2	6.0'	20.5'	4.0'	5.9'	88.4	4.2'	6.9'
	10.0'	61.3	6.0'	6.0'		10.0'	4.7'	39.6	7.0'	8.4'	5.0'	10.6'	20.0	7.5'	25.6'	5.0'	6.9'	56.6	5.3'	8.7'
	11.0'	48.6	6.8'	6.8'		11.0'	5.3'	31.4	7.8'	9.5'	6.0'	12.3'	13.9	8.9'	30.7'	6.0'	7.9'	39.3	6.3'	10.4'
	12.0'	39.4	7.5'	7.5'		12.0'	5.8'	25.5	8.7'	10.5'	7.0'	14.0'	10.2	10.4'	35.8'	7.0'	8.9'	28.9	7.4'	12.1'

LCALDJ5W-L25UE-DUN-1C1N (Track)

System Power :	30.0W
Test Date :	8/31/2018
Beam Angle 50% :	40.9°
Field Angle 10% :	71.3°
Color Temp. (CCT) :	3000K
CRI :	90
Lumens Delivered :	2286
CBP :	3999
Power Factor :	> 0.9

MULTIPLIERS

LUMENS

3500lm (-L35): 1.41

2500lm (-L25): 1.00

CRI

CCT

90 CRI: 1.00

97 CRI: 0.89

4000K: 1.02

3500K: 1.01

3000K: 1.00

2700K: 0.96

Track (-1C1N, -2C2N, & -3C1N)	8.0'	80.3	5.3'	5.3'		8.0'	4.1'	51.5	6.1'	7.4'	3.0'	6.1'	55.5	4.5'	15.4'	3.0'	3.9'	157.1	3.2'	5.2'
	9.0'	61.6	6.0'	6.0'		9.0'	4.7'	39.5	7.0'	8.5'	4.0'	7.8'	31.2	6.0'	20.5'	4.0'	4.9'	88.4	4.2'	6.9'
	10.0'	48.7	6.8'	6.8'		10.0'	5.3'	31.3	7.8'	9.5'	5.0'	9.6'	20.0	7.5'	25.6'	5.0'	5.9'	56.6	5.3'	8.7'
	11.0'	39.5	7.5'	7.5'		11.0'	5.8'	25.4	8.7'	10.5'	6.0'	11.3'	13.9	8.9'	30.7'	6.0'	6.9'	39.3	6.3'	10.4'
	12.0'	32.7	8.2'	8.2'		12.0'	6.4'	21.1	9.6'	11.6'	7.0'	13.0'	10.2	10.4'	35.8'	7.0'	7.9'	28.9	7.4'	12.1'