


LCMPDSS12RPW-T30, 2000lm, 3000K

System Power:	22.5W	MULTIPLIERS	
Test Date:	1/2017	4000K:	1.07
Beam Angle 50%:	111.6°	3500K:	1.04
Field Angle 10%:	161.8°	3000K:	1.00
Color Temperature:	3000K		
CRI :	90		
Lumens Delivered:	1824.9lm		
CBCP:	641cd		
Power Factor:	>.90		




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	17.7'	17.8
8.0'	23.5'	10.0
10.0'	29.4'	6.4
12.0'	35.3'	4.5
14.0'	41.2'	3.3

LCMPD12RPW-T40, 2000lm, 4000K

System Power:	22.2W	MULTIPLIERS	
Test Date:	1/2017	4000K:	1.00
Beam Angle 50%:	112.7°	3500K:	0.97
Field Angle 10%:	162.0°	3000K:	0.93
Color Temperature:	4000K		
CRI :	90		
Lumens Delivered:	1961.9lm		
CBCP:	681cd		
Power Factor:	>.90		



FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	18.0'	18.9
8.0'	24.0'	10.6
10.0'	30.0'	6.8
12.0'	36.1'	4.7
14.0'	42.1'	3.5