


LCRMPD5R - PHOTOMETRY

ROUND 5" LUMENPAD RECESSED

LCRMPD5RW-T30 - 1100lm - 3000K

System Power	:11.3W	Multipliers	
Test Date	:1/2016	4000K	1.33
Beam Angle 50%	:109.4°	3500K	1.16
Field Angle 10%	:160.8°	2700K	0.90
Color Temperature	:3000K		
CRI	:90		
Lumens Delivered	:884.4lm		
CBCP	:318cd		
Power Factor	:> 0.90		

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
8.0'	22.6'	5.0
9.0'	25.4'	3.9
10.0'	28.2'	3.2
11.0'	31.1'	2.6
12.0'	33.9'	2.2

LCRMPD5RW-T40 - 1100lm - 4000K

System Power	:11.2W	Multipliers	
Test Date	:1/2016	3500K	0.86
Beam Angle 50%	:109.4°	3000K	0.75
Field Angle 10%	:160.8°	2700K	0.68
Color Temperature	:4000K		
CRI	:90		
Lumens Delivered	:953.3lm		
CBCP	:343cd		
Power Factor	:> 0.90		

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
8.0'	22.6'	5.4
9.0'	25.4'	4.2
10.0'	28.2'	3.4
11.0'	31.1'	2.8
12.0'	33.9'	2.4

LCRMPD5RWUE-D10-T40 - 1100lm - 4000K

System Power	:11.2W	Multipliers	
Test Date	:6/2017	3500K	0.90
Beam Angle 50%	:113.5°	3000K	0.77
Field Angle 10%	:165.8°	2700K	0.69
Color Temperature	:3908K		
CRI	:90		
R9 Value	:13.8		
Lumens Delivered	:1196lm		
CBCP	:407cd		
Power Factor	:0.98		

CANDELA TABULATION



FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
8.0'	24.4'	6.4
9.0'	27.5'	5.0
10.0'	30.5'	4.1
11.0'	33.6'	3.4
12.0'	36.6'	2.8