


LCRMPD7R - PHOTOMETRY

ROUND 7" LUMENPAD RECESSED

LCRMPD7RW-T30 - 1400lm - 3000K

System Power	:14.0W	Multipliers	
Test Date	:1/2016	4000K	1.33
Beam Angle 50%	:108.7°	3500K	1.17
Field Angle 10%	:160.6°	2700K	0.90
Color Temperature	:3000K		
CRI	:90		
Lumens Delivered	:1102.6lm		
CBCP	:400cd		
Power Factor	:> 0.90		

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	16.7'	11.1
8.0'	22.3'	6.3
10.0'	27.9'	4.0
12.0'	33.5'	2.8
14.0'	39.0'	2.0

LCRMPD7RW-T35 - 1400lm - 3500K

System Power	:12.8W	Multipliers	
Test Date	:1/2017	4000K	1.09
Beam Angle 50%	:116.5°	3000K	0.82
Field Angle 10%	:166.4°	2700K	0.73
Color Temperature	:3675K		
CRI	:90		
R9 Value	:18.7		
Lumens Delivered	:1188lm		
CBCP	:389cd		
Power Factor	:0.99		

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	19.4'	10.8
8.0'	25.9'	6.1
9.0'	29.1'	4.8
11.0'	35.6'	3.2
12.0'	38.8'	2.7

LCRMPD7RW-T40 - 1400lm - 4000K

System Power	:13.9W	Multipliers	
Test Date	:1/2016	3500K	0.86
Beam Angle 50%	:109.6°	3000K	0.75
Field Angle 10%	:161.0°	2700K	0.68
Color Temperature	:4000K		
CRI	:90		
Lumens Delivered	:1188lm		
CBCP	:389cd		
Power Factor	:0.99		

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	17.0'	12.7
8.0'	22.7'	7.2
10.0'	28.4'	4.6
12.0'	34.0'	3.2
14.0'	39.7'	2.3

LCMPD7RWUE-D10-T40 - 1400lm - 4000K

System Power	:14.0W	Multipliers	
Test Date	:6/2017	3500K	0.89
Beam Angle 50%	:114.7°	3000K	0.76
Field Angle 10%	:162.7°	2700K	0.69
Color Temperature	:3939K		
CRI	:90		
R9 Value	:15.1		
Lumens Delivered	:1410lm		
CBCP	:478cd		
Power Factor	:0.98		

CANDELA TABULATION



FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	18.7'	13.3
8.0'	25.0'	7.5
10.0'	31.2'	4.8
12.0'	37.5'	3.3
14.0'	43.7'	2.4