


LRALD471SWF350 - 40W/3500LM - 3000K

System Power	:12.0W	Multipliers	
Test Date	:6/2014	4000K	1.04
Color Temperature	:3000K	3500K	1.02
CRI	:80	2700K	0.95
Lumens Delivered	:2046Lm	2500K	0.45
CBCP	:2912cd	1700K	0.42
CRI			
		80CRI (Blank)	:1.00
		90CRI (-C90)	:0.71
		97CRI (-C97)	:0.73

CANDELA TABULATION



PERFORMANCE DATA

LUMINAIRE SPACED 2' FROM WALL

Single Unit						DISTANCE FROM CEILING	Multiple Units On 2" Centers			Multiple Units On 3" Centers			Multiple Units On 4" Centers		
Lateral Distance From Fixture 2" From Wall							Spaced 2' From Wall			Spaced 2' From Wall			Spaced 2' From Wall		
0'	1'	2'	3'	4'	5'										
4.2	0.7	0.3	0.4	0.2	0.1	1'	5.3	2.4	5.3	5.1	0.4	5.1	4.6	0.8	4.6
72.6	40.3	8.4	1.2	0.3	0.2	2'	90.1	83.3	90.1	75.3	40.4	75.3	73.3	17	73.3
62.8	50.7	26.8	4.2	0.8	0.1	3'	118.1	110.2	118.1	71.4	82.4	71.4	64.6	53.9	64.6
44.1	34.2	22.8	11.2	2.1	0.5	4'	94.1	91.9	94.1	67	58.6	67	48.5	45.9	48.5
32	24.6	16.2	10.5	4.8	1.2	5'	74.3	72.5	74.3	53.8	44.9	53.8	41.7	33.2	41.7
22.1	17.7	11.8	7.9	5.3	2.2	6'	57.1	55.7	57.1	39.4	37	39.4	33	25.1	33
15	12.5	8.8	6.1	4.3	2.9	7'	42.2	43.1	42.2	29.6	29	29.6	24	20	24
10.4	9	6.6	4.7	3.4	2.5	8'	32.2	32.5	32.2	23.4	22.3	23.4	17.8	16.8	17.8
7.3	6.5	5.1	3.8	2.8	2.1	9'	24.6	24.8	24.6	18.2	17.7	18.2	13.7	13.5	13.7
5.3	4.8	3.9	3	2.8	1.8	10'	19	19.2	19	14.3	14.4	14.3	11.1	10.8	11.1

LUMINAIRE SPACED 3' FROM WALL

Single Unit						DISTANCE FROM CEILING	Multiple Units On 3" Centers			Multiple Units On 4" Centers			Multiple Units On 5" Centers		
Lateral Distance From Fixture 3" From Wall							Spaced 3' From Wall			Spaced 3' From Wall			Spaced 3' From Wall		
0'	1'	2'	3'	4'	5'										
0.1	0.3	0.4	0.3	0.2	0.1	1'	0.9	1.3	0.9	0.5	1.1	0.5	0.4	0.8	0.4
8.8	6.9	2.9	0.5	0.2	0.1	2'	10.1	10.2	10.1	9.2	6	9.2	9.1	2.9	9.1
32.3	25.1	11.5	3.7	1	0.3	3'	40	37	40	34.4	23.3	34.4	33	13.7	33
31.6	28.4	21.4	7.9	2.4	0.7	4'	47.9	53.6	47.9	36.6	43.4	36.6	33.2	30.2	33.2
24.7	21.8	17.3	12.2	5.3	1.4	5'	50.3	44.5	50.3	35.4	35.8	35.4	27.7	29.8	27.7
19.6	17.2	13.3	10.1	6.9	3.2	6'	41.8	40.8	41.8	33.6	28.7	33.6	26	23.9	26
15.9	13.8	10.6	8.1	6	3.9	7'	35.8	35.2	35.8	28.5	24.9	28.5	23.9	19.4	23.9
12.6	11.1	8.5	6.5	4.9	3.7	8'	30.5	29.5	30.5	23.3	21.9	23.3	20.2	16.2	20.2
9.8	8.8	6.9	5.3	4	3.1	9'	25.4	24.8	25.4	19.2	18.9	19.2	16.3	14.1	16.3
7.6	6.9	5.6	4.3	3.3	2.6	10'	20.8	20.9	20.8	16.2	15.7	16.2	13.3	12.5	13.3

*Based on a minimum of five luminaires. Light Loss Factor: 1. Values are rounded to nearest 1/10th footcandle.