


LRALD6021 - PHOTOMETRY

6" ARCHITECTURAL LED GLASS DECO OPEN

LRALD6021350SWF-T40-FR - 4000lm - Flood - 4000K

System Power	:43.4W	Multipliers	
Test Date	:3/19/2019	CCT Multipliers	
Beam Angle 50%	:32.5°	4000K	1.00
Field Angle 10%	:59.5°	3000K	0.97
Color Temperature	:4165K	2700K	0.94
CRI	:86.7	CRI Multipliers	
R9 Value	:26.3	80 CRI	:1.00
Lumens Delivered	:3658lm	97 CRI	:0.77
CBCP	:8911		
Power Factor	:1.00		

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
20.0'	11.7'	22.3
25.0'	14.6'	14.3
30.0'	17.5'	9.9
35.0'	20.4'	7.3
40.0'	23.3'	5.6

LRALD6021350SWF-B60-T40-FR - 4000lm - Flood - 4000K

System Power	:43.5W	Multipliers	
Test Date	:3/19/2019	CCT Multipliers	
Beam Angle 50%	:46.5°	4000K	1.00
Field Angle 10%	:95.0°	3000K	0.97
Color Temperature	:4069K	2700K	0.94
CRI	:86	CRI Multipliers	
R9 Value	:22.7	80 CRI	:1.00
Lumens Delivered	:2682lm	97 CRI	:0.77
CBCP	:3119		
Power Factor	:0.99		

CANDELA TABULATION



FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
8.0'	6.9'	48.7
12.0'	10.3'	21.7
16.0'	13.7'	12.2
20.0'	17.2'	7.8
24.0'	20.6'	5.4