


LRLD4W-QC-T30 - 10W/650lm- 3000K

System Power	:10.4W	Multipliers	
Test Date	:09/2017	4000K	1.33
Beam Angle 50%	:100.1°	2700K	1.99
Field Angle 10%	:146.8°	CRI	
Color Temperature	:3000K	80CRI (Blank)	:0.89
CRI	:90	90CRI (-C90)	:1.00
Lumens Delivered	:637.7lm	97CRI (-C97)	:1.08
CBCP	:273cd		

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	14.3'	7.6
7.0'	16.7'	5.6
8.0'	19.1'	4.3
9.0'	21.5'	3.4
10.0'	23.9'	2.7

LRLD4W-QC-T40 - 10W/650lm- 4000K

System Power	:11.6W	Multipliers	
Test Date	:09/2017	3000K	1.30
Beam Angle 50%	:102.8°	2700K	0.99
Field Angle 10%	:147.6°	CRI	
Color Temperature	:4000K	80CRI (Blank)	:0.89
CRI	:90	90CRI (-C90)	:1.00
Lumens Delivered	:696lm	97CRI (-C97)	:1.08
CBCP	:285cd		

CANDELA TABULATION



FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	15.0'	7.9
7.0'	17.5'	5.8
8.0'	20.0'	4.5
9.0'	22.5'	3.5
10.0'	25.1'	2.9