


LTD5120 - PHOTOMETRY

20W/1,400LM LINEAR LED WALL WASH


LTD5120W-DLV - 1,400LM/20W - 3,000K

System Power	:19.1W
Test Date	:9/2016
Input Voltage	:120.0V
Color Temperature	:3,088K
CRI	:84.1
R9 Value	:15.8
Lumens Delivered	:1,395Lm
CBCP	:462cd
Power Factor	:0.96

CANDELA TABULATION



TRACK 3' FROM WALL



19W LED
CCT: 3,088K

DISTANCE FROM CEILING


Single Fixture Performance

	0'	1'	2'	3'	4'	5'
1'	41.3	33.7	20.3	10.7	5.6	3
2'	35.4	29.8	19.1	10.9	6.1	3.4
3'	23.1	20.4	14.5	9.2	5.5	3.3
4'	13.8	12.7	9.9	6.9	4.5	2.9
5'	8.3	7.8	6.5	4.9	3.5	2.4
6'	5.2	4.9	4.3	3.4	2.6	1.9
7'	3.4	3.3	2.9	2.4	2	1.5
8'	2.3	2.2	2	1.8	1.5	1.2
9'	1.6	1.6	1.5	1.3	1.1	0.9

Multiple Fixture Performance*

4'	5'	6'
54	44.6	54
48	31.6	48
43	31.6	43
30.7	25.8	30.7
20.7	19.1	20.7
14.1	13.7	14.1
10	9.9	10
7.3	7.3	7.3
5.5	5.5	5.5
4.2	4.3	4.2
3.6	3.6	3.6

TRACK 4' FROM WALL



19W LED
CCT: 3,088K

DISTANCE FROM CEILING

Single Fixture Performance

	0'	1'	2'	3'	4'	5'
1'	23	20.4	14.9	9.6	5.6	3.6
2'	22.1	19.8	14.8	9.9	6.3	3.9
3'	17.4	15.9	12.5	8.8	5.9	3.9
4'	12.3	11.4	9.4	7.1	5	3.5
5'	8.3	7.9	6.8	5.4	4	2.9
6'	5.6	5.4	4.8	4	3.1	2.4
7'	3.9	3.8	3.4	2.9	2.4	1.9
8'	2.8	2.7	2.5	2.2	1.9	1.5
9'	2	2	1.8	1.6	1.4	1.2

Multiple Fixture Performance*

4'	5'	6'
37	35.2	37
31.2	27	31.2
27.7	21.6	27.7
26.4	24.5	26.4
20.5	19.8	20.5
15.5	15.3	15.5
11.7	11.7	11.7
9	9	9
7.6	7.6	7.6
5.9	5.9	5.9
4.7	4.7	4.7

*Based on a minimum of five luminaires. Light Loss Factor: 1. Values are rounded to nearest 1/10th footcandle.